

Super Patch



Modified epoxy repair patch



SUPER PATCH is an easy-to-use epoxy product for repair and resurfacing of concrete. Great when fast repairs are needed in high traffic areas. **SUPER PATCH** is a one-step process with a fast set-up and cure time that significantly reduces or eliminates the need for down time. Can also be used as patching in freezers and cold storage areas, as mortar to repair loose bricks or blocks, and as a general cement adhesive. **SUPER PATCH** is many times stronger and more durable than concrete.

Directions: Sweep and clean area to be repaired with Omega's **CON RENEW**. Allow area to dry completely. Mix parts A and B thoroughly until uniform in color. If using partial kit use 2 parts Resin to 1 part Hardener. Pot life approximately 90 minutes. Add aggregate to A & B mixture. Aggregate amount can be varied to match desired viscosity of mixture. For cracks, apply to area and smooth. To resurface, apply with trowel and skim coat to 1/16 inch. Cure time 12-24 hours depending on temperature of air and surface. Heat may be applied to decrease cure time. Not recommended for wood or asphalt surfaces.

Areas of Use:

- *apartment complexes
- *hotels
- *hospitals
- *amusement parks
- *warehouses
- *industrial facilities
- *grounds maintenance

Health	2
Flammability	1
Reactivity	0
Protection	B

Appearance and odor.....	Clear yellow liquid and Granular solid
Specific Gravity.....	Liquid - 1.06 -2.65
VOC.....	Passes AQMD rule 1162
NFPA Fire Rating.....	Flammable

ONLY OMEGA™

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134