




Section 1 ~ Identification

| | |
|--|--|
| Identity (As Used On Label and List) A1048 ACOUSTA TILE | Date Prepared: 09-19-2017 |
| Company Information: OMEGA INDUSTRIAL SUPPLY, INC | Emergency Telephone Number: 1-800-424-9300 |
| Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1 | Telephone Number for Information: 1-800-571-7347 |
| (City, State, and Zip Code) Fairfield, CA 94534 | Signature of Prepare (Optional) REGULATORY DEPT. |

Section 2 ~ Hazard(s) Identification

| | | |
|--|---|-----------------------------|
| Physical Hazards | Flammable aerosols Category 1 | |
| Health Hazards | Serious eye damage/eye irritation | Category 2A |
| | Carcinogenicity | Category 2 |
| | Reproductive toxicity (the unborn child) | Category 2 |
| | Specific target organ toxicity, repeated exposure | Category 2 |
| OSHA Defined Hazards | Not classified. | |
| Label Elements |    | Signal Word: Danger. |
| Hazard Statement | Extremely flammable aerosol. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. | |
| Precautionary Statement | | |
| Prevention | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. | |
| Response | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. | |
| Storage | Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. | |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. | |
| Environmental Health | Hazardous to the aquatic environment, acute hazard | Category 3 |
| | Hazardous to the aquatic environment, long-term hazard | Category 3 |
| Hazard(s) not Otherwise Classified (HNOC) | Harmful to aquatic life. Harmful to aquatic life with long lasting effects. | |
| Supplemental Information | None | |

Section 3 ~ Composition/Information on Ingredients

| Chemical Name | Common Name & Synonyms | CAS No. | % (Wt.) |
|--|------------------------|------------|----------|
| Butane | | 106-97-8 | 20 – 40 |
| Ethyl Alcohol | | 64-17-5 | 20 – 40 |
| Acetone | | 67-64-1 | 10 – 20 |
| Magnesium Silicate | | 14807-96-6 | 10 – 20 |
| Propane | | 74-98-6 | 2.5 – 10 |
| Titanium Dioxide | | 13463-67-7 | 2.5 – 10 |
| Toluene | | 108-88-3 | 2.5 – 10 |
| Other components below reportable levels | | | 10 – 20 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Skin Contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most Important Symptoms/Effects, Acute and Delayed: Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Prolonged exposure may cause chronic effects.

Indication of Immediate Medical Attention and Special Treatment Needed:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General Information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical:

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental Precautions: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Level 2 Aerosol.

Conditions for Safe Storage, Including Any Incompatibilities: Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|-------------------------------|------|------------------------|------------|
| Acetone (67-64-1) | PEL | 2400 mg/m3 1000 ppm | |
| Ethyl Alcohol (64-17-5) | PEL | 1900mg/m3 1000 ppm | |
| Propane (74-98-6) | PEL | 1800 mg/m3 1000 ppm | |
| Titanium Dioxide (13463-67-7) | PEL | 15 mg/m3 | Total dust |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--------------------|---------|---------|------|
| Toluene (108-88-3) | Ceiling | 300 ppm | |
| | TWA | 200 ppm | |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---------------------------------|------|-----------|------------|
| Magnesium Silicate (14807-96-6) | TWA | 0.3 mg/m3 | Total dust |
| | | 0.1 mg/m3 | Respirable |
| | | 20 mppcf | |
| | | 2.4 mppcf | Respirable |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---------------------------------|------|----------|---------------------|
| Acetone (67-64-1) | STEL | 500 ppm | |
| | TWA | 250 ppm | |
| Butane (106-97-8) | STEL | 1000 ppm | |
| Ethyl Alcohol (64-17-5) | STEL | 1000 ppm | |
| Magnesium Silicate (14807-96-6) | TWA | 2 mg/m3 | Respirable fraction |
| Titanium Dioxide (13463-67-7) | TWA | 10 mg/m3 | |
| Toluene (108-88-3) | TWA | 20 ppm | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---------------------------------|------|------------------------|------------|
| Acetone (67-64-1) | TWA | 590 mg/m3 250 ppm | |
| Butane (106-97-8) | TWA | 1900 mg/m3 800 ppm | |
| Ethyl Alcohol (64-17-5) | TWA | 1900 mg/m3 1000 ppm | |
| Magnesium Silicate (14807-96-6) | TWA | 2 mg/m3 | Respirable |
| Propane (74-98-6) | TWA | 1800 mg/m3 1000 ppm | |
| Toluene (108-88-3) | STEL | 560 mg/m3 150 ppm | |
| | TWA | 375 mg/m3 100 ppm | |

Biological Limit Values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|--------------------|-----------|---------------------------|---------------------|---------------|
| Acetone (67-64-1) | 25 mg/l | Acetone | Urine | * |
| Toluene (108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | 0.03 mg/l | Toluene | Urine | * |
| | 0.02 mg/l | Toluene | Blood | * |

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (108-88-3) Skin designation applies.

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other: Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical and Chemical Properties

| | | |
|-----------------------------|--|---|
| Appearance | Evaporation Rate: Not available. | Solubility(ies) |
| Physical State: Gas. | Flammability (solid, gas): Not available. | Solubility (water): Not available. |

| | | |
|--|---|--|
| Form: Aerosol. | Upper/Lower Flammability or Explosive Limits | Partition Coefficient (n-octanol/water): Not available. |
| Color: Not available. | Flammability Limit – Lower (%): 3.4 % estimated | Auto-Ignition Temperature: 699.8 °F (371 °C) estimated |
| Odor: Not available. | Flammability Limit – Upper (%): 10.7 % estimated | Decomposition Temperature: Not available. |
| Odor Threshold: Not available. | Explosive Limit - Lower (%): Not available. | Viscosity: Not available. |
| pH: Not available. | Explosive Limit - Upper (%): Not available. | Other Information |
| Melting Point/Freezing Point: Not available. | Vapor Pressure: 82.56 psig @70F estimated | Explosive Properties: Not explosive. |
| Initial Boiling Point and Boiling Range: 179.76°F (82.09°C) estimated | Vapor Density: Not available. | Oxidizing Properties: Not oxidizing. |
| Flash Point: -156.0 °F (-104.4 °C) Propellant estimated | Relative Density: Not available. | Specific Gravity: 1.072 estimated |

Section 10 ~ Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible Materials: Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous Decomposition Products: No hazardous decomposition products are known.

Section 11 ~ Toxicological Information

Information on Likely Routes of Exposure

Inhalation: May cause damage to organs through prolonged or repeated exposure by inhalation.

Skin Contact: No adverse effects due to skin contact are expected.

Eye Contact: Causes serious eye irritation.

Ingestion: Expected to be a low ingestion hazard.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Information on Toxicological Effects

Acute Toxicity:

| <u>Components</u> | <u>Species</u> | <u>Test Results</u> |
|-------------------------------|----------------|--------------------------|
| Acetone (67-64-1) | | |
| Acute Dermal | | |
| LD50 | Guinea Pig | > 7426 mg/kg, 24 Hours |
| | Rabbit | > 9.4 ml/kg, 24 Hours |
| | | > 7426 mg/kg, 24 Hours |
| | | > 9.4 ml/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | 55700 ppm, 3 Hours |
| | | 132 mg/l, 3 Hours |
| | | 50.1 mg/l |
| Oral | | |
| LD50 | Rat | 5800 mg/kg |
| | | 2.2 ml/kg |
| Butane (106-97-8) | | |
| Acute Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes |
| | Rat | 52 %, 120 Minutes |
| | | 1355 mg/l |
| Ethyl Alcohol (64-17-5) | | |
| Acute Inhalation | | |
| LC50 | Cat | 85.41 mg/l, 4.5 Hours |
| | Mouse | 43.68 mg/l, 6 Hours |
| | | > 60000 ppm |
| | Rat | 79.43 mg/l, 134 Minutes |
| | | > 115.9 mg/l, 4 Hours |
| | | 51.3 mg/l, 6 Hours |
| Oral | | |
| LD50 | Monkey | 6000 mg/kg |
| | Mouse | 10500 ml/kg |
| | Pig | > 5000 mg/kg |
| | Rat | 10470 mg/kg |
| | | 7800 ml/kg |
| Propane (74-98-6) | | |
| Acute Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes |
| | Rat | 52 %, 120 Minutes |
| | | 1355 mg/l |
| | | 658 mg/l/4h |
| Titanium Dioxide (13463-67-7) | | |
| Acute Inhalation | | |
| LC50 | Rat | > 2.28 mg/l, 4 Hours |
| Oral | | |
| LD50 | Mouse | > 5000 mg/kg |
| | Rat | > 2000 mg/kg |
| Toluene (108-88-3) | | |
| Acute Dermal | | |
| LD50 | Rabbit | > 5000 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Mouse | 6405 - 7436 ppm, 6 Hours |
| | | 5320 ppm, 8 Hours |
| | | 5879 - 6281 ppm, 6 Hours |
| | | 25.7 mg/l, 4 Hours |

Oral
LD50 Rat > 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Not applicable.

Serious Eye Damage/Eye Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization

Respiratory Sensitization: Not a respiratory sensitizer.

Skin Sensitization: This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Magnesium Silicate (14807-96-6) 2B Possibly carcinogenic to humans.
3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (13463-67-7) 2B Possibly carcinogenic to humans.

Toluene (108-88-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens: Not listed.

Reproductive Toxicity: Suspected of damaging the unborn child.

Specific Target Organ Toxicity - Single Exposure: Not classified.

Specific Target Organ Toxicity - Repeated Exposure: May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard: Not likely, due to the form of the product.

Chronic Effects: May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Section 12 ~ Ecological Information

Ecotoxicity: Harmful to aquatic life with long lasting effects.

| Components | Species | Test Results |
|-------------------------------|---|-----------------------------|
| Acetone (67-64-1) | | |
| Aquatic | | |
| Crustacea | EC50 Water flea (Daphnia magna) | 21.6 - 23.9 mg/l, 48 hours |
| Fish | LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |
| Ethyl Alcohol (64-17-5) | | |
| Aquatic | | |
| Crustacea | EC50 Water flea (Daphnia magna) | 7700 - 11200 mg/l, 48 hours |
| Fish | LC50 Fathead minnow (Pimephales promelas) | > 100.1 mg/l, 96 hours |
| Titanium Dioxide (13463-67-7) | | |
| Aquatic | | |
| Crustacea | EC50 Water flea (Daphnia magna) | > 1000 mg/l, 48 hours |
| Fish | LC50 Mummichog (Fundulus heteroclitus) | > 1000 mg/l, 96 hours |
| Toluene (108-88-3) | | |
| Aquatic | | |
| Algae | IC50 Algae | 433.0001 mg/L, 72 Hours |
| Crustacea | EC50 Daphnia | 7.645 mg/L, 48 Hours |
| | Water flea (daphnia magna) | 5.46 - 9.83 mg/l, 48 hours |
| Fish | LC50 CoHo salmon, silver salmon (oncorhynchus kisutch) | 8.11 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24

Butane 2.89

Ethyl Alcohol -0.31

Propane 2.36

Toluene 2.73

Mobility in Soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal Instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations: Dispose in accordance with all applicable regulations.

Hazardous Waste Code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from Residues / Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Section 14 ~ Transportation Information

| DOT | IATA | IMDG |
|--|--|--|
| UN Number: UN1950 | UN Number: UN1950 | UN Number: UN1950 |
| UN Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity) | UN Proper Shipping Name: Aerosols, flammable | UN Proper Shipping Name: AEROSOLS |
| Transport Hazard Class(es) | Transport Hazard Class(es) | Transport Hazard Class(es) |
| Class: 2.1 | Class: 2.1 | Class: 2.1 |
| Subsidiary Risk - | Subsidiary Risk - | Subsidiary Risk - |
| Label(s): 2.1 | Label(s) 2.1 | Label(s) 2.1 |
| Packing Group: Not applicable. | Packing Group: Not applicable. | Packing Group: Not applicable. |
| Special Precautions for User: Not available. | Environmental Hazards: No. | Marine Pollutant: No. |
| Special Provisions: N82 | ERG Code: 10L | Environmental Hazards |
| Packaging Exceptions: 306 | Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling. | EmS: F-D, S-U |
| Packaging Non Bulk: None | Passenger and Cargo Aircraft: Allowed with restrictions. | Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling. |
| Packaging Bulk: None | Other Information | Packaging Exceptions: LTD QTY |
| | Cargo Aircraft Only: Allowed with restrictions. | Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable. |
| | Packaging Exceptions: LTD QTY | |

DOT



IATA;IMDG



Section 15 ~ Regulatory Information

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous CERCLA Hazardous

Acetone (CAS 67-64-1) Listed.

Toluene (CAS 108-88-3) Listed.

SARA 304 Emergency Release Notification: Not regulated

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard Categories:
 Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely Hazardous Substance: Not listed

SARA 311/312 Hazardous Chemical: No

SARA 313 (TRI reporting)

| Chemical Name | CAS number | % by wt. |
|---------------|------------|----------|
| Toluene | 108-88-3 | 2.5 – 10 |

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Toluene (108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Butane (106-97-8) Propane (74-98-6)

Safe Drinking Water Act (SDWA): Not regulated

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (67-64-1) 6532

Toluene (108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (67-64-1) 35 % WV

Toluene (108-88-3) 35 % WV

DEA Exempt Chemical Mixtures Code Number

Acetone (67-64-1) 6532

Toluene (108-88-3) 594

US State Regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (67-64-1)

Butane (106-97-8)

Magnesium Silicate (14807-96-6)

Titanium Dioxide (13463-67-7)

Toluene (108-88-3)

US. Massachusetts RTK - Substance List

Acetone (67-64-1)

Butane (106-97-8)

Ethyl Alcohol (64-17-5)

Magnesium Silicate (14807-96-6)

Propane (74-98-6)

Titanium Dioxide (13463-67-7)

Toluene (108-88-3)

US. New Jersey Worker and Community

Right-to-Know Act

Acetone (67-64-1)

Butane (106-97-8)

Ethyl Alcohol (64-17-5)

Magnesium Silicate (14807-96-6)

Propane (74-98-6)

Titanium Dioxide (13463-67-7)

Toluene (108-88-3)

US. Pennsylvania Worker and

Community Right-to-Know Law

Acetone (67-64-1)

Butane (106-97-8)

Ethyl Alcohol (64-17-5)

Magnesium Silicate (14807-96-6)

Propane (74-98-6)

Titanium Dioxide (13463-67-7)

Toluene (108-88-3)

US. Rhode Island RTK

Acetone (67-64-1)

Butane (106-97-8)

Propane (74-98-6)

Toluene (108-88-3)

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

| | NFPA | HMIS | Key |
|------------------|------|------|-------------------------|
| HEALTH | 2 | 2* | 4= Severe |
| FLAMMABILITY | 3 | 3 | 3= Serious |
| REACTIVITY | 0 | X | 2= Moderate |
| OTHER/PROTECTION | - | - | 1= Slight 0= Minimal |

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.