

ACOUSTA TILE

White Color
Acoustical Tile
Restorer



ACOUSTA TILE restores stained and discolored tile to a like-new condition. Eliminates the need for costly ceiling tile replacement. Does not affect acoustical properties. Excellent for both smooth and rough surfaces. Will not cause warp or sag. Coating is non-flammable when dry and does not change the fire rating of the tile to which it has been applied.

SURFACE PREPARATION:

Remove loose dust and dirt by wiping tile gently with a dry rag or duster. Cover surfaces under area to be treated with newspaper or a drop cloth. Protect other areas with masking tape. Tile must be dry. Leaks which have caused water stains must be repaired prior to application.

DIRECTIONS:

SHAKE VIGOROUSLY BEFORE AND DURING USE. Replace button with large vertical action actuator for application on installed tile. When possible, remove tiles to a well ventilated area before application. Shake can vigorously until agitator ball rattles freely. Continue shaking for at least one minute. Hold can 8 to 10 inches from tiles to be coated. Apply with a sweeping motion using several thin coats. Allow each coat to dry for at least two minutes before applying next coat. If coating runs, can is too close to surface. Feather edges into the remainder of the ceiling by holding can further away during application.

IMPORTANT:

After application, clean valve by turning can upside down and applying short burst to clear actuator.

Health	2
Flammability	3
Physical Hazard	0
Protection	B

Areas of Use:

- *Damage Restoration Companies
- *Hospitals
- *Hotels
- *Municipalities
- *Office Buildings
- *Schools

Appearance & Odor.....	White Spray with hydrocarbon odor
VOC%.....	51%
Net Contents.....	12 OZ. (340 Grams)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631