

Section 1 ~ Identification

Identity (As Used On Label and List) A1122 AIR TOOL REJUVENATOR	Date Prepared: 07/26/23	Date Revised: 04/06/26
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300	
Address (Number, Street, Suite/Apt#) 1133 WEST 27 TH STREET	Telephone Number for Information: 1-800-571-7347	
(City, State, and Zip Code) CHEYENNE, WY 82001	Signature of Prepare (Optional) REGULATORY DEPT.	

Section 2 ~ Hazard(s) Identification

Classifications Flammable Aerosol: Category 1 Gases Under Pressure: Liquefied Gas

Label Elements



Signal Word: WARNING

Hazard Statement

Flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary Statement

Keep away from heat, sparks, open flames or hot surfaces. -No smoking. Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

Other Hazards

N/A

Unknown acute toxicity (GHS US)

0%

Section 3 ~ Composition/Information on Ingredients

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Carbon dioxide	124-38-9	1-3%
Distillates (petroleum), hydrotreated light	64742-47-8	45-55%

Section 4 ~ First Aid Measures

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Not a likely exposure route. If a large quantity of liquid is swallowed, do not induce vomiting, call a physician or poison control center.

INHALATION: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision.

SKIN: Defatting and dermatitis.

INHALATION: Irritation.

ORAL: Abdominal irritation, nausea, vomiting, and diarrhea.

CHRONIC HEALTH HAZARDS: Repeated or prolonged contact may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis.

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. There is no specific treatment regimen. Treatment of overexposure should be directed toward the control of symptoms and the clinical condition of the patient.

Section 5 ~ Firefighting Measures

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water fog.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLAMMABLE. Contents under pressure. Exposure to temperatures above 120 °F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Cool containers with water spray.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.

Section 6 ~ Accidental Release Measures

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Use non-combustible material like vermiculite, sand or earth on spill sweep to clean. Dispose in accordance with local, state and federal laws.

Small releases may be wiped up with wiping material.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection.

Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Section 7 ~ Handling and Storage

HANDLING AND STORAGE: Pressurized container: Do not pierce or bum, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in cool, dry, ventilated area.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: None known.

Section 8 ~ Exposure Controls/Personal Protection

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Carbon dioxide	5000 ppm	5000 ppm
Distillates (petroleum), hydrotreated light	Not Established	200mg/m ³

Section 9 ~ Physical and Chemical Properties

APPEARANCE: Milky tan liquid.	ODOR: Oily.	ODOR THRESHOLD: N/D
pH: N/A	MELTING POINT/FREEZING POINT: N/D	INITIAL BOILING POINT AND BOILING RANGE: N/D
FLASH POINT: N/D	EVAPORATION RATE: N/D	FLAMMABILITY (solid/gas): Flammable aerosol.
LOWER FLAMMABILITY LIMIT: N/D	UPPER FLAMMABILITY LIMIT: N/D	EXPLOSIVE LIMIT LOWER (%): N/D
EXPLOSIVE LIMIT UPPER (%): N/D	VAPOR PRESSURE (mm Hg): N/D	VAPOR DENSITY (AIR=1): N/D
RELATIVE DENSITY (H ₂ O=1): 0.83 - 0.86 g/ml @ 77° F (25° C)	SOLUBILITY(IES): 0%	
PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D		AUTOIGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/D		VISCOSITY: N/D

Section 10 ~ Stability and Reactivity

REACTIVITY: None known.	CHEMICAL STABILITY: Stable.	POSSIBLE HAZARDOUS REACTIONS: None known.
CONDITIONS TO AVOID: Temperatures greater than 122 °F (50 °C) and sources of ignition.		INCOMPATIBLE MATERIALS: None known.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.		

Section 11 ~ Toxicological Information

TOXICOLOGICAL INFORMATION: Distillates (petroleum), hydrotreated light (64742-47-8): LD₅₀ (Oral, Rat) 5 g/kg; LD₅₀ (Dermal, Rabbit) 2 g/kg; LC₅₀ (Inhalation, Rat, 4h) 5 mg/L. Carbon dioxide (124-38-9): LC₅₀ (Inhalation, Rat, 30m) 470,000 ppm.

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation, burning, redness, tearing.

INGESTION: May cause gastrointestinal irritation, nausea, diarrhea, vomiting, abdominal cramps.

INHALATION: Unlikely due to low vapor pressure. Mist may cause respiratory tract irritation, headache.

SKIN: May cause mild irritation, localized defatting, repeated prolonged contact may cause allergic reaction in some individuals.

MEDICAL CONDITION AGGRAVATED: May aggravate existing dermatitis.

ACUTE HEALTH HAZARDS

Eyes: redness, tearing, blurred vision. **Skin:** defatting and dermatitis. **Inhalation:** Irritation. **Oral:** abdominal irritation, nausea, vomiting, and diarrhea.

CHRONIC HEALTH HAZARDS: Repeated or prolonged contact may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis.

CARCINOGENICITY

OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

Section 12 ~ Ecological Information

ECOTOXICITY: Distillates (petroleum), hydrotreated light (64742-47-8): LC₅₀ (Daphnia, 48h) > 1000 mg/L; EC₅₀ (Algae, 72h) >1000 mg/L.

PERSISTENCE AND DEGRADABILITY: This product is biodegradable. **BIOACCUMULATIVE POTENTIAL:** This product is not expected to bioaccumulate.

MOBILITY IN SOIL: No additional information available.

OTHER ADVERSE EFFECTS: An environmental hazard cannot be excluded in the event of improper handling or disposal.

Section 13 ~ Disposal Considerations

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Section 14 ~ Transportation Information

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.	AIR SHIPMENT	SHIPPING BY WATER
HAZARD CLASS/DIVISION: 2.1	PROPER SHIPPING NAME: Aerosols, Flammable	VESSEL (IMO/IMDG)
UN/NA NUMBER: UN1950	HAZARD CLASS/DIVISION: 2.1	PROPER SHIPPING NAME: Aerosols
PACKING GROUP: N/A	UN/NA NUMBER: UN1950	HAZARD CLASS/DIVISION: 2.1
	PACKING GROUP: N/A	UN/NA NUMBER: UN1950
		PACKING GROUP: N/A
		ENVIRONMENTAL HAZARDS WATER: N/A

Section 15 ~ Regulatory Information

TSCA STATUS: All chemicals are listed or exempt. **CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** None

SARA 311/312 HAZARD CATEGORIES: Fire Hazard

SARA 313 REPORTABLE INGREDIENTS: This product does not contain any chemical components with known CAS numbers that exceed the threshold (*de minimis*) reporting levels established by SARA Title III, Section 313.

STATE REGULATIONS: California Proposition 65: None. **INTERNATIONAL REGULATIONS:** No information available

VOLATILE ORGANIC COMPOUNDS (VOC): 15.19%

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	1	1	4= Severe
FLAMMABILITY	2	2	3= Serious
REACTIVITY	0	0	2= Moderate
PERSONAL PROTECTION	N/A	B	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and -may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet