

# ALL WEATHER PATCH

## Asphalt Roof Patch



**ALL WEATHER PATCH** is a pliable asphalt roof patch that can be used on damp as well as dry surfaces. **ALL WEATHER PATCH** is ideal for many roof repairs and for stopping roof leaks around vent pipes, spouts, valleys, skylights, gutters and chimneys. Use for the construction and repair of flashings, but not on rubber membranes or EPDM roofing systems. It may also be used to seal cracks in exterior chimneys, walls, foundation joints and for lining leaking gutters and troughs.

**ALL WEATHER PATCH** is not paintable.

**PREPARATION:** Surfaces must be clean and free of surface rust and loose material. Apply **ALL WEATHER PATCH** when surface temperatures are between 50 °F and 120 °F. In colder weather (50 °F and below), **ALL WEATHER PATCH** should be stored in heated room (70 °F to 80 °F.) at least 24 hours prior to application to promote ease of application. **ALL WEATHER PATCH** is formulated to be used year round.

**APPLICATION:** Apply generously with a trowel or putty knife. It is highly recommended to reinforce the repair with a strip of universal patching fabric. Work material to an even consistency over and into the area to be repaired approximately 1/8" to 1/2" thick, two or three inches beyond the problem area. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line. Allow product to cure a minimum of 30 - 60 days prior to application of reflective coating.

**COVERAGE RATE:** One gallon covers approximately 12 sq. ft. when applied 1/8" thick.

**CLEAN-UP:** Clean tools or spills with mineral spirits.

Health	2
Flammability	3
Physical Hazard	0
Protection	-

**Areas of Use:**

- \*Hotels
- \*Schools
- \*Cities & Counties
- \*Restaurants
- \*Stadiums
- \*Casinos
- \*Amusement Parks

Appearance & Odor.....	Black paste with petroleum solvent odor
Net Contents.....	5 Gallons

## OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 307-514-0631