

Section 1 ~ Identification

Identity (As Used On Label and List) B4217 AQUAMAN	Date Prepared: 07/25/22
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 1133 WEST 27 TH STREET	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) CHEYENNE, WY 82001	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Classifications

SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 37.1% (oral), 83.4% (dermal), 91.6% (inhalation)

Label Elements



Signal Word: DANGER

Hazard Statement

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause cancer.

Precautionary Statement

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing dust. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements: Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Emits toxic fumes when heated.

Other Hazards

None Known.

Unknown acute toxicity (GHS US)

N/A

Section 3 ~ Composition/Information on Ingredients

Substance/mixture: Mixture

Ingredient name	%	CAS number
Talc, not containing asbestiform fibres	≥20 - ≤50	14807-96-6
glass, oxide, chemicals	≥10 - ≤20	65997-17-3
Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-ω-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	≥10 - ≤20	72244-98-5
bis-[4-(2,3-epoxipropoxy)phenyl]propane	≥5.0 - ≤10	1675-54-3
titanium dioxide	≥5.0 - ≤10	13463-67-7
Phenol, polymer with formaldehyde, glycidyl ether (MW≤700)	≥1.0 - ≤5.0	28064-14-4
crystalline silica, respirable powder (<10 microns)	<1.0	14808-60-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4 ~ First Aid Measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Potential acute health effects

Eye contact: Causes serious eye irritation.

Inhalation: May cause respiratory irritation.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following: pain or irritation, watering, redness

Inhalation: Adverse symptoms may include the following: respiratory tract irritation, coughing

Skin contact: Adverse symptoms may include the following: irritation, redness

Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5 ~ Firefighting Measures

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media: None known.

Specific hazards arising from the chemical: No specific fire or explosion hazard.

Hazardous thermal decomposition products: Decomposition products may include the following materials: carbon oxides, nitrogen oxides, sulfur oxides, metal oxide/oxides

Special protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6 ~ Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7 ~ Handling and Storage

Protective measures: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage including any incompatibilities: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8 ~ Exposure Controls/Personal Protection

Control parameters - Occupational exposure limits

Ingredient name

Talc , not containing asbestiform fibres

Exposure limits

ACGIH TLV (United States, 1/2021).

TWA: 2 mg/m³ 8 hours. Form: Respirable

OSHA PEL Z3 (United States).

TWA: 2 mg/m³

glass, oxide, chemicals

OSHA PEL (United States).

TWA: 15 mg/m³

TWA: 5 mg/m³ Form: Respirable

TWA: 15 mg/m³ Form: Total dust

ACGIH TLV (United States).

TWA: 1 f/cc Form: Continuous filament glass fibers

TWA: 5 mg/m³, (Inhalable) Form: Continuous filament glass fibers

TWA: 3 mg/m³ Form: Respirable

TWA: 10 mg/m³ Form: Total dust

ACGIH TLV (United States, 1/2021).

[Continuous filament glass fibers]

TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction

TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 µm; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.

Poly[oxy(methyl-1,2-ethanediy)], α-hydro-ω-hydroxy-, ether with 2,2-bis (hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether

None.

bis-[4-(2,3-epoxipropoxy)phenyl]propane

None.

titanium dioxide

TWA: 15 mg/m³ 8 hours. Form: Total dust

ACGIH TLV (United States, 1/2021).

TWA: 10 mg/m³ 8 hours.

OSHA PEL (United States, 5/2018).

Phenol, polymer with formaldehyde, glycidyl ether (MW<=700)

None.

crystalline silica, respirable powder (<10 microns)

ACGIH TLV (United States, 1/2021). [Silica, crystalline]

TWA: 0.025 mg/m³ 8 hours. Form: Respirable

OSHA PEL Z3 (United States, 6/2016).

TWA: 10 mg/m³ / (%SiO₂+2) 8 hours. Form: Respirable

TWA: 250 mppcf / (%SiO₂+5) 8 hours. Form: Respirable

OSHA PEL (United States, 5/2018). [Silica, crystalline]

TWA: 50 µg/m³ 8 hours. Form: Respirable dust

Key to abbreviations

A = Acceptable Maximum Peak

ACGIH = American Conference of Governmental Industrial Hygienists.

C = Ceiling Limit

F = Fume

IPEL = Internal Permissible Exposure Limit

OSHA = Occupational Safety and Health Administration.

R = Respirable

Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

S = Potential skin absorption

SR = Respiratory sensitization

SS = Skin sensitization

STEL = Short term Exposure limit values

TD = Total dust

TLV = Threshold Limit Value

TWA = Time Weighted Average

Consult local authorities for acceptable exposure limits.

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace procedures atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection: Chemical splash goggles.

Skin protection

Hand protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves: butyl rubber

Body protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9 ~ Physical and Chemical Properties

Physical state: Solid.

Color: Not available.

Odor: Not available.

Odor threshold: Not available.

pH: Not applicable.

Melting point: Not available.

Boiling point: Not available.

Flash point: Closed cup: Not applicable.

Auto-ignition temperature: Not applicable.

Decomposition temperature: Not available.

Flammability (solid, gas): Not available.

Lower and upper explosive (flammable) limits: Not applicable.

Evaporation rate: Not available.

Vapor pressure: Not available.

Vapor density: Not applicable.

Relative density: 1.97

Density (lbs / gal): 16.44

Solubility: Insoluble in the following materials: cold water.

Partition coefficient: n-octanol/water: Not applicable.

Viscosity: Kinematic (40°C (104°F)): Not applicable.

Volatility: 0% (v/v), 0% (w/w)

% Solid. (w/w): 100

Section 10 ~ Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides metal oxide/oxides.

Section 11 ~ Toxicological Information

Acute toxicity

<u>Product/ingredient name</u>	<u>Result</u>	<u>Species</u>	<u>Dose</u>	<u>Exposure</u>
bis-[4-(2,3-epoxipropoxy) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Conclusion/Summary: There are no data available on the mixture itself.

Irritation/Corrosion

<u>Product/ingredient name</u>	<u>Result</u>	<u>Species</u>	<u>Score</u>	<u>Exposure</u>	<u>Observation</u>
bis-[4-(2,3-epoxipropoxy) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary

Skin: There are no data available on the mixture itself.

Eyes: There are no data available on the mixture itself.

Respiratory: There are no data available on the mixture itself.

Sensitization

<u>Product/ingredient name</u>	<u>Route of exposure</u>	<u>Species</u>	<u>Result</u>
bis-[4-(2,3-epoxipropoxy) phenyl]propane	skin	Mouse	Sensitizing

Conclusion/Summary

Skin: There are no data available on the mixture itself.

Respiratory: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Classification

<u>Product/ingredient name</u>	<u>OSHA</u>	<u>IARC</u>	<u>NTP</u>
glass, oxide, chemicals	-	3	-
bis-[4-(2,3-epoxipropoxy) phenyl]propane	-	3	-
titanium dioxide	-	2B	-
crystalline silica, respirable powder (<10 microns)	-	1	Known to be a human carcinogen.

Carcinogen Classification code

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

<u>Name</u>	<u>Category</u>	<u>Route of exposure</u>	<u>Target organs</u>
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

<u>Name</u>	<u>Category</u>	<u>Route of exposure</u>	<u>Target organs</u>
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-

Target organs: Contains material which may cause damage to the following organs: lungs, cardiovascular system, upper respiratory tract, skin, eyes.

Aspiration hazard: Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact: Causes serious eye irritation.

Inhalation: May cause respiratory irritation.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following: pain or irritation, watering, redness

Inhalation: Adverse symptoms may include the following: respiratory tract irritation, coughing

Skin contact: Adverse symptoms may include the following: irritation, redness

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary: There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects: There are no data available on the mixture itself.

Potential delayed effects: There are no data available on the mixture itself.

Long term exposure

Potential immediate effects: There are no data available on the mixture itself.

Potential delayed effects: There are no data available on the mixture itself.

Potential chronic health effects

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: No known significant effects or critical hazards.

Reproductive toxicity: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

<u>Product/ingredient name</u>	<u>Oral (mg/kg)</u>	<u>Dermal (mg/kg)</u>	<u>Inhalation (gases) (ppm)</u>	<u>Inhalation (vapors) (mg/l)</u>	<u>Inhalation (dusts and mists) (mg/l)</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	15000	15000	15000	15000	15000

Section 12 ~ Ecological Information

Toxicity

<u>Product/ingredient name</u>	<u>Result</u>	<u>Species</u>	<u>Exposure</u>
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water Chronic NOEC 0.3 mg/l	Daphnia - daphnia magna Daphnia	48 hours 21 days
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

Persistence and degradability

<u>Product/ingredient name</u>	<u>Aquatic half-life</u>	<u>Photolysis</u>	<u>Biodegradability</u>
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partitioncoefficient (Koc): Not available.

Section 13 ~ Disposal Considerations

Disposal methods: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.
Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14 ~ Transportation Information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

DOT: None identified.
IMDG: None identified.
IATA: None identified.

Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments: Not applicable.

Section 15 ~ Regulatory Information

United States

United States inventory (TSCA 8b): All components are active or exempted.

SARA 302/304

SARA 304 RQ: 276014.4 lbs / 125310.5 kg

Composition/information on ingredients

Name	EHS	(lbs)	SARA 302 TPQ (gallons)	(lbs)	SARA 304 RQ (gallons)
Phenol	Yes.	500/1000	-	1000	-

SARA 311/312

Classification: SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Composition/information on ingredients

<u>Name</u>	<u>%</u>	<u>Classification</u>
Talc , not containing asbestiform fibres	≥20 - ≤50	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-ω-hydroxy-, ether with 2, 2-bis(hydroxymethyl) 1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	≥10 - ≤20	SKIN SENSITIZATION - Category 1B
bis-[4-(2,3-epoxipropoxy)phenyl] propane	≥5.0 - ≤10	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B
titanium dioxide	≥5.0 - ≤10	CARCINOGENICITY - Category 2
Phenol, polymer with formaldehyde, glycidyl ether (MW≤700)	≥1.0 - ≤5.0	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B
crystalline silica, respirable powder (<10 microns)	<1.0	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your suppliers representative.

California Prop. 65



WARNING: Cancer - www.P65Warnings.ca.gov.

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	2	2*	4= Severe
FLAMMABILITY	0	0	3= Serious
INSTABILITY	0		2= Moderate
PHYSICAL HAZARD		0	1= Slight
			0= Minimal

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Key to abbreviations:

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and -may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet