

C PATCH

Concrete Filler
and Sealant



C PATCH is an extremely elastic moisture cure sealant designed for application to dry or damp surfaces common to roofing, driveways, sidewalks, plaza decks, balconies, stairwells, parking structures, roof decks and surrounding pools & fountains. This unique product fills and adheres to concrete, masonry, wood, stone, asphalt and metallic surfaces including difficult surfaces such as Kynar 500 PVDF and other anodized metals. **C PATCH** is 100% solids and will not shrink. This product cures rapidly to a solid rubber seal that can accommodate up to 50% joint movement making it the ideal product for many expansion joints. Product will not bubble when applied to damp concrete. Meets USDA Requirements for Non-food contact applications.

DIRECTIONS:

Clean surface and remove any finishes, dirt, oil, wax, oxidation, loose paint or debris from working surfaces. Pre-clean surface with **MEGA POWER** or similar water based cleaner followed by a water rinse or Isopropyl Alcohol. Do not use petroleum solvents to clean prior to application. For best results apply at temperatures above 32°F (0°C). Product can be tooled for 15 minutes after application. **NOTE:** For application at temperatures below 35°F, surface must be dry and free of any frost or ice as this will prevent bonding to substrate.

Health	1
Flammability	0
Physical Hazard	0
Protection	-

Areas of Use:

- *Apartment Complexes
- *Cities & Counties
- *Utility Companies
- *Industrial Facilities
- *Plumbing Departments
- *Grounds Maintenance
- *Warehouses
- *Hospitals

Appearance & Odor.....	Paste with mild mint scent
VOC%.....	2.23%
Net Contents.....	10.1 OZ (300 ml)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631