

### Section 1 ~ Identification

<b>Identity (As Used On Label and List)</b> <b>A1126R COAT IT - RED</b>	<b>Date Prepared:</b> 05-23-2016
<b>Company Information:</b> OMEGA INDUSTRIAL SUPPLY, INC	<b>Emergency Telephone Number:</b> 1-800-424-9300
<b>Address (Number, Street, Suite/Apt#)</b> 101 Grobric Ct #1	<b>Telephone Number for Information:</b> 1-800-571-7347
<b>(City, State, and Zip Code)</b> Fairfield, CA 94534	<b>Signature of Prepare (Optional)</b> REGULATORY DEPT.

### Section 2 ~ Hazard(s) Identification

<b>Physical Hazards</b>	Flammable aerosols	Category 1
<b>Health Hazards</b>	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
<b>OSHA Defined Hazards</b>	Not classified	

<b>Label Elements</b>	 	<b>Signal Word:</b> Danger
-----------------------	---	----------------------------

**Hazard Statement** Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

#### Precautionary Statement

<b>Prevention</b>	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection /face protection.
<b>Response</b>	<b>If inhaled:</b> Remove person to fresh air and keep comfortable for breathing. <b>If in eyes:</b> Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.

<b>Hazard(s) Not Otherwise Classified (HNOC)</b>	None known.	<b>Supplemental Information</b>	None
--	-------------	---------------------------------	------

### Section 3 ~ Composition/Information on Ingredients

Mixtures	CAS No.	%(Wt.)
<b>Chemical Name</b>		
Acetone	67-64-1	10 - 20
Propane	74-98-6	10 - 20
Barium Sulfate, Natural	7727-43-7	2.5 - 10
Butane	106-97-8	2.5 - 10
Ethylene Glycol Propyl Ether	2807-30-9	2.5 - 10
Methyl Isobutyl Ketone	108-10-1	2.5 - 10
Methyl Propyl Ketone	107-87-9	2.5 - 10
Propylene Glycol Monomethyl Ether Acetate	108-65-6	2.5 - 10
Isobutyl Acetate	110-19-0	1 - 2.5
Xylene	1330-20-7	1 - 2.5
Other components below reportable levels		20 - 40

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### Section 4 ~ First Aid Measures

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**Skin Contact:** Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Ingestion:** In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

**Most Important Symptoms/Effects, Acute and Delayed:** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Indication of Immediate Medical Attention and Special Treatment Needed:** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General Information:** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### Section 5 ~ Fire Fighting Measures

**Suitable Extinguishing Media:** Alcohol resistant foam. Powder. Carbon dioxide (CO2).

**Unsuitable Extinguishing Media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific Hazards Arising from The chemical:** Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

**Special Protective Equipment and Precautions for Firefighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Fire-Fighting Equipment/Instructions:** Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods:** Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

**General Fire Hazards:** Extremely flammable aerosol.

### Section 6 ~ Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures:** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and Materials for Containment and Cleaning Up:** Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental Precautions:** Avoid discharge into drains, water courses or onto the ground.

**Section 7 ~ Handling and Storage**

**Precautions for Safe Handling:** Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for Safe Storage, Including Any Incompatibilities:** Level 2 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

**Section 8 ~ Exposure Controls/Personal Protection****Occupational Exposure Limits:****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Acetone (67-64-1)	PEL	2400 mg/m <sup>3</sup> 1000 ppm	
Barium Sulfate, Natural (7727-43-7)	PEL	5mg/m <sup>3</sup> 15 mg/m <sup>3</sup>	Respirable fraction Total dust
Isobutyl Acetate (110-19-0)	PEL	700 mg/m <sup>3</sup> 150 ppm	
Methyl Isobutyl Ketone (108-10-1)	PEL	410 mg/m <sup>3</sup> 100 ppm	
Methyl Propyl Ketone (107-87-9)	PEL	700 mg/m <sup>3</sup> 200 ppm	
Propane (74-98-6)	PEL	1800 mg/m <sup>3</sup> 1000 ppm	
Xylene (1330-20-7)	PEL	435 mg/m <sup>3</sup> 100 ppm	

**US. ACGIH Threshold Limit Values (Cont.)**

Components	Type	Value	Form
Methyl Propyl Ketone (107-87-9)	STEL	150 ppm	
Xylene (1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Acetone (67-64-1)	TWA	590 mg/m <sup>3</sup> 250 ppm	
Barium Sulfate, Natural (7727-43-7)	TWA	5 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>	Respirable. Total
Butane (106-97-8)	TWA	1900 mg/m <sup>3</sup> 800 ppm	
Isobutyl Acetate (110-19-0)	TWA	700 mg/m <sup>3</sup> 150 ppm	
Methyl Isobutyl Ketone (108-10-1)	STEL	300 mg/m <sup>3</sup> 75 ppm	
	TWA	205 mg/m <sup>3</sup> 50 ppm	
Methyl Propyl Ketone (107-87-9)	TWA	530 mg/m <sup>3</sup> 150 ppm	
Propane (74-98-6)	TWA	1800 mg/m <sup>3</sup> 1000 ppm	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Acetone (67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Barium Sulfate, Natural (7727-43-7)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction
Butane (106-97-8)	STEL	1000ppm	
Isobutyl Acetate (110-19-0)	TWA	150 ppm	
Methyl Isobutyl Ketone (108-10-1)	STEL	75 ppm	
	TWA	20 ppm	

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
Propylene Glycol Monomethyl Ether Acetate (108-65-6)	TWA	50 ppm

**Biological Limit Values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (67-64-1)	25 mg/l	Acetone	Urine	*
Methyl Isobutyl Ketone (108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
Xylene (1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure Guidelines****US - California OELs: Skin designation**

Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) Can be absorbed through the skin.

**Appropriate engineering controls** – Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual Protection Measures, Such as Personal Protective Equipment**

**Eye/Face Protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection**

**Hand Protection:** Wear appropriate chemical resistant gloves.

**Other:** Wear suitable protective clothing.

**Respiratory Protection:** If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal Hazards:** Wear appropriate thermal protective clothing, when necessary.

**General Hygiene Considerations:** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Section 9 ~ Physical Chemical Properties****Appearance**

**Physical State:** Gas.

**Form:** Aerosol.

**Color:** Not available.

**Odor:** Not available.

**Odor Threshold:** Not available.

**pH:** Not available.

**Melting Point/Freezing Point:** Not available.

**Initial Boiling Point and Boiling Range:** -47.2°F (-44°C) supplier estimated

**Flash Point:** -2.2 °F (-19.0 °C) supplier

**Evaporation Rate:** Not available.

**Flammability (solid, gas):** Not available.

**Flammability Limit – Lower (%):** 1.7 supplier

**Flammability Limit – Upper (%):** 10.9 supplier

**Explosive Limit - Lower (%):** Not available.

**Explosive Limit - Upper (%):** Not available.

**Vapor Pressure:** Not available.

**Vapor Density:** Not available.

**Relative Density:** Not available.

**Solubility (Water):** Not available.

**Partition Coefficient (n-octanol/water):** Not available.

**Auto-Ignition Temperature:** Not available.

**Decomposition Temperature:** Not available.

**Viscosity:** Not available.

**Specific Gravity:** 0.815 estimated

**Section 10 ~ Stability and Reactivity**

**Reactivity:** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical Stability:** Material is stable under normal conditions.

**Possibility of Hazardous Reactions:** Hazardous polymerization does not occur.

**Conditions to Avoid:** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible Materials:** Strong acids. Strong oxidizing agents. Nitrates. Aluminum. Halogens. Phosphorus. Fluorine. Chlorine.

**Hazardous Decomposition Products:** No hazardous decomposition products are known.

**Section 11 ~ Toxicological Information****Information on Likely Routes of Exposure**

**Inhalation:** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

**Eye Contact:** Causes serious eye irritation.

**Skin Contact:** No adverse effects due to skin contact are expected.

**Ingestion:** Expected to be a low ingestion hazard.

**Symptoms Related to The Physical, Chemical and Toxicological Characteristics:** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Information On Toxicological Effects**

**Acute Toxicity:** Narcotic effects

<u>Components</u>	<u>Species</u>	<u>Test Results</u>
<b>Acetone (67-64-1)</b>		
<b>Acute</b>		
Dermal, LD50	Guinea pig	> 7426 mg/kg, 24 Hours; > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours; > 9.4 ml/kg, 24 Hours
Inhalation, LC50	Rat	55700 ppm, 3 Hours; 132 mg/l, 3 Hours; 50.1 mg/l
Oral, LD50	Rat	5800 mg/kg; 2.2 ml/kg
<b>Barium Sulfate, Natural (7727-43-7)</b>		
<b>Acute</b>		
Oral, LD100	Rat	564 g/kg
LD50	Rat	307 g/kg
<b>Butane (106-97-8)</b>		
<b>Acute</b>		
Inhalation, LC50	Mouse	1237 mg/l, 120 Minutes; 52 %, 120 Minutes
	Rat	1355 mg/l
<b>Ethylene Glycol Propyl Ether (2807-30-9)</b>		
<b>Acute</b>		
Dermal, LD50	Guinea pig	5.6 g/kg, 4 Days
	Rabbit	> 1 g/kg, 24 Hours, 1337 ml/kg, 14 Days
Inhalation, LC50	Rat	> 2132 ppm, 6 Hours; > 1800 ppm
Oral, LD50	Guinea pig	2.2 g/kg
	Mouse	1774 mg/kg
	Rat	0.5 - 1 g/kg
<b>Isobutyl Acetate (110-19-0)</b>		
<b>Acute</b>		
Dermal, LD50	Rabbit	> 17400 mg/kg, 24 Hours
Inhalation, LC50	Rat	> 30 mg/l, 6 Hours; > 23.4 mg/l, 4 Hours
Oral, LD50	Rat	13413 mg/kg
<b>Methyl Isobutyl Ketone (108-10-1)</b>		
<b>Acute</b>		
Inhalation, LC50	Rat	2000 - 4000 ppm, 4 Hours
Oral, LD50	Rat	2.08 g/kg
<b>Methyl Propyl Ketone (107-87-9)</b>		
<b>Acute</b>		
Inhalation Vapor LC50	Rat	>25.5 mg/l, 4 Hours
Oral LD50	Mouse	1600 mg/kg
	Rat	1600 - 3200 mg/kg
<b>Propane (74-98-6)</b>		
<b>Acute</b>		
Inhalation, LC50	Mouse	1237 mg/l, 120 Minutes, 52 %, 120 Minutes
	Rat	1355 mg/l; 658 mg/l/4h
<b>Propylene Glycol Monomethyl Ether Acetate (108-65-6)</b>		
<b>Acute</b>		
Dermal, LD50	Rat	> 2000 mg/kg, 24 Hours
Oral, LD50	Rat	>5000 mg/kg; > 14.1 ml
<b>Xylene (1330-20-7)</b>		
<b>Acute</b>		
Dermal, LD50	Rabbit	> 5000 ml/kg, 4 Hours; 12126 mg/kg, 24 Hours
Inhalation, LC50	Rat	5922 ppm, 4 Hours
Oral, LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg; 10 ml/kg

\* Estimates for product may be based on additional component data not shown.

**Skin Corrosion/Irritation:** Prolonged skin contact may cause temporary irritation.

**Serious Eye Damage/Eye Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization**

**Respiratory Sensitization:** Not a respiratory sensitizer.

**Skin Sensitization:** This product is not expected to cause skin sensitization.

**Germ Cell Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity:** Risk of cancer cannot be excluded with prolonged exposure.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Methyl Isobutyl Ketone (CAS 108-10-1) 2B Possibly carcinogenic to humans.

Xylene (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens:** Not listed.

**Reproductive Toxicity:** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

**Specific Target Organ Toxicity - Single Exposure:** May cause drowsiness and dizziness.

**Specific Target Organ Toxicity - Repeated Exposure:** Not classified.

**Aspiration Hazard:** Not likely, due to the form of the product.

**Chronic Effects:** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

**Section 12 ~ Ecological Information**

**Ecotoxicity:** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

<u>Components</u>	<u>Species</u>	<u>Test Results</u>
<b>Acetone (67-64-1)</b>		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, Donaldson trout (Oncorhynchus mykiss)
<b>Barium Sulfate, Natural (7727-43-7)</b>		
<b>Aquatic</b>		
Crustacea	EC50	Tubificid worm (Tubifex tubifex)
<b>Methyl Isobutyl Ketone (108-10-1)</b>		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas)
<b>Methyl Propyl Ketone (107-87-9)</b>		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas)
<b>Propylene Glycol Monomethyl Ether Acetate (108-65-6)</b>		
<b>Aquatic</b>		
Crustacea	EC50	Daphnia
<b>Xylene (1330-20-7)</b>		

*Aquatic  
Fish*

LC50

Bluegill (*Lepomis macrochirus*)

7.711 - 9.591 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and Degradability:** No data is available on the degradability of this product.

**Bioaccumulative Potential**

**Partition Coefficient n-octanol / water (log Kow)**

Acetone	-0.24	Methyl Isobutyl ketone	1.31	Xylene	3.12 – 3.2
Butane	2.89	Methyl Propyl Ketone	0.91		
Isobutyl Acetate	1.78	Propane	2.36		

**Mobility in Soil:** No data available

**Other Adverse Effects:** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**Section 13 ~ Disposal Considerations**

**Disposal Instructions:** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local Disposal Regulations:** Dispose in accordance with all applicable regulations.

**Hazardous Waste Code:** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from Residues / Unused Products:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated Packaging:** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

**Section 14 ~ Transport Information**

US Depart. of Transportation (DOT)	Water Transportation (IMDG)	Air Transportation (IATA)
<b>Proper Shipping Name:</b> Aerosols, flammable, (each not exceeding 1 L capacity) <b>Hazard Class:</b> 2.1 <b>UN Number:</b> UN1950 <b>Packing Group:</b> N/A <b>Labels:</b> 2.1 <b>Special Provisions:</b> N82 <b>Packaging Exceptions:</b> 306 <b>Packaging Non Bulk:</b> None <b>Packaging Bulk:</b> None	<b>Proper Shipping Name:</b> AEROSOLS <b>Hazard Class:</b> 2.1 <b>UN Number:</b> UN1950 <b>Packing Group:</b> N/A <b>Labels:</b> 2.1 <b>Environmental Hazards:</b> <b>Marine Pollutant:</b> No <b>Packaging Exceptions:</b> Ltd. Qty <b>EmS:</b> F-D, S-U	<b>Proper Shipping Name:</b> Aerosols, flammable <b>Hazard Class:</b> 2.1 <b>UN Number:</b> UN1950 <b>Packing Group:</b> N/A <b>Labels:</b> 2.1 <b>Environmental Hazards:</b> No <b>Packaging Exceptions:</b> Ltd. Qty. <b>ERG Code:</b> 10L <b>Passenger and Cargo Aircraft:</b> Allowed with restrictions. <b>Cargo Aircraft Only:</b> Allowed with restrictions.

**Special precautions for user:** Read safety instructions, SDS and emergency procedures before handling.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not applicable.

DOT

IATA;IMDG



**Section 15 ~ Regulatory Information**

**US Federal Regulations:** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication. Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):** Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetone (67-64-1)	Listed.	Isobutyl Acetate (110-19-0)	Listed.
Methyl Isobutyl Ketone (108-10-1)	Listed.	Xylene (1330-20-7)	Listed.

**SARA 304 Emergency Release Notification:** Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

Hazard categories Immediate Hazard – Yes	Delayed Hazard – No
Fire Hazard – Yes	Pressure Hazard – No
Reactivity Hazard – No	

**SARA 302 Extremely Hazardous Substance:** Not listed.

**SARA 311/312 Hazardous Chemical:** No.

**SARA 313 (TRI Reporting)**

Chemical Name	CAS Number	% By Wt.
Methyl Isobutyl Ketone	108-10-1	2.5 – 10
Xylene	1330-20-7	1 – 2.5

**Other Federal Regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Methyl Isobutyl Ketone (108-10-1) Xylene (1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (106-97-8) Propane (74-98-6)

**Safe Drinking Water Act (SDWA):** Not regulated.

**Drug Enforcement Administration (DEA), List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Acetone (67-64-1) 6532 Methyl Isobutyl Ketone (108-10-1) 6715

**Drug Enforcement Administration (DEA), List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Acetone (67-64-1) 35 % WV Methyl Isobutyl Ketone (108-10-1) 35 % WV

**DEA Exempt Chemical Mixtures Code Number**

Acetone (67-64-1) 6532 Methyl Isobutyl Ketone (108-10-1) 6715

**US State Regulations**

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100):** Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Acetone (67-64-1) Butane (106-97-8) Methyl Isobutyl Ketone (108-10-1)

**US. Massachusetts RTK - Substance List**

Acetone (67-64-1)  
Barium Sulfate, Natural (7727-43-7)  
Butane (106-97-8)  
Isobutyl Acetate (110-19-0)  
Methyl Isobutyl Ketone (108-10-1)  
Methyl Propyl Ketone (107-87-9)  
Propane (74-98-6)  
Xylene (1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

Acetone (67-64-1)  
Barium Sulfate, Natural (7727-43-7)  
Butane (106-97-8)  
Isobutyl Acetate (110-19-0)  
Methyl Isobutyl Ketone (108-10-1)  
Methyl Propyl Ketone (107-87-9)  
Propane (74-98-6)  
Xylene (1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Acetone (67-64-1)  
Barium Sulfate, Natural (7727-43-7)  
Butane (106-97-8)  
Isobutyl Acetate (110-19-0)  
Methyl Isobutyl Ketone (108-10-1)  
Methyl Propyl Ketone (107-87-9)  
Propane (74-98-6)  
Xylene (1330-20-7)

Xylene (1330-20-7)

**US. Rhode Island RTK**

Acetone (67-64-1)  
Butane (106-97-8)  
Isobutyl Acetate (110-19-0)  
Methyl Isobutyl Ketone (108-10-1)  
Propane (74-98-6)  
Xylene (1330-20-7)

**US - California Proposition 65** WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic Substance:** Methyl Isobutyl Ketone (108-10-1)

Listed: November 4, 2011

**US - California Proposition 65 - CRT: Listed date/Developmental toxin:** Methyl Isobutyl Ketone (108-10-1)

Listed: March 28, 2014

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	2	2	4= Severe
FLAMMABILITY	4	4	3= Serious
REACTIVITY	1	2	2= Moderate
OTHER/PROTECTION	-	X	1= Slight 0= Minimal

Disclaimer: Omega Industrial Supply, Inc. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.