

Section 1 ~ Identification

Identity (As Used On Label and List)

A1126Y COAT IT YELLOW

Date Prepared:

03-02-2015

Company Information:

OMEGA INDUSTRIAL SUPPLY, INC

Emergency Telephone Number:

1-800-424-9300

Address (Number, Street, Suite/Apt#)

101 Grobric Ct #1

Telephone Number for Information:

1-800-571-7347

(City, State, and Zip Code)

Fairfield, CA 94534

Signature of Prepare (Optional)

REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Physical Hazards

Flammable aerosols

Category 1

Gases under pressure

Liquefied gas

Health Hazards

Serious eye damage/eye irritation

Category 2A

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Environmental Hazards

Not classified.

OSHA Defined Hazards

Not classified.

Label Elements



Signal Word: Danger.

Hazard Statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary Statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection.

Response

If inhaled: Remove person to fresh air and keep comfortable for breathing. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not Otherwise Classified (HNOC)

None known.

Supplemental Information

None.

Section 3 ~ Composition/Information on Ingredients

Mixtures

Chemical Name	Common Name & Synonyms	CAS No.	%(Wt.)
Acetone		67-64-1	10 - 20
Propane		74-98-6	10 - 20
Barium Sulfate, Natural		7727-43-7	2.5 - 10
Butane		106-97-8	2.5 - 10
Ethylene Glycol Propyl Ether		2807-30-9	2.5 - 10
Isobutyl Acetate		110-19-0	2.5 - 10
Methyl Isobutyl Ketone		108-10-1	2.5 - 10
Methyl Propyl Ketone		107-87-9	2.5 - 10
Titanium Dioxide		13463-67-7	2.5 - 10
Propylene Glycol Monomethyl Ether Acetate		108-65-6	1 - 2.5
Xylene		1330-20-7	1 - 2.5
Other components below reportable levels			20 - 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye Contact: Rinse with water. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

Most Important Symptoms/Effects, Acute and Delayed: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of Immediate Medical Attention and Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General Information: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Powder. Alcohol resistant foam. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media: None known.

Specific Hazards Arising from the Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-Fighting Equipment/Instructions: In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions for Safe Handling: Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for Safe Storage, Including Any Incompatibilities: Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Acetone (67-64-1)	PEL	2400 mg/m3 1000 ppm	
Barium Sulfate, Natural (7727-43-7)	PEL	5 mg/m3 15 mg/m3	Respirable fraction Total dust.
Isobutyl Acetate (110-19-0)	PEL	700 mg/m3 150 ppm	
Methyl Isobutyl Ketone (108-10-1)	PEL	410 mg/m3 100 ppm	
Methyl Propyl Ketone (107-87-9)	PEL	700 mg/m3 200 ppm	
Propane (74-98-6)	PEL	1800 mg/m3 1000 ppm	
Titanium Dioxide (13463-67-7)	PEL	15 mg/m3	Total Dust
Xylene (1330-20-7)	PEL	435 mg/m3 100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (67-64-1)	STEL TWA	750 ppm 500 ppm	
Barium Sulfate, Natural (7727-43-7)	TWA	5 mg/m3	Inhalable fraction
Butane (106-97-8)	STEL	1000 ppm	
Isobutyl Acetate (110-19-0)	TWA	150 ppm	
Methyl Isobutyl Ketone (108-10-1)	STEL TWA	75 ppm 20 ppm	
Methyl Propyl Ketone (107-87-9)	STEL	150 ppm	
Titanium Dioxide (13463-67-7)	TWA	10 mg/m3	
Xylene (1330-20-7)	STEL TWA	150 ppm 100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Acetone (67-64-1)	TWA	590 mg/m3 250 ppm	
Barium Sulfate, Natural (7727-43-7)	TWA	5 mg/m3 10 mg/m3	Respirable Total
Butane (106-97-8)	TWA	1900 mg/m3 800 ppm	
Isobutyl Acetate (110-19-0)	TWA	700 mg/m3 150 ppm	
Methyl Isobutyl Ketone (108-10-1)	STEL TWA	300 mg/m3 75 ppm 205 mg/m3	
Methyl Propyl Ketone (107-87-9)	TWA	50 ppm 530 mg/m3	
Propane (74-98-6)	TWA	1800 mg/m3 1000 ppm	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Propylene Glycol Monomethyl Ether Acetate (108-65-6)	TWA	50 ppm	

Biological Limit Values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (67-64-1)	50 mg/l	Acetone	Urine	*
Methyl Isobutyl Ketone (108-10-1)	1 mg/l	Methyl Isobutyl Ketone	Urine	*
Xylene (1330-20-7)	1.5 g/g	Methylhippuric Acids	Creatinine in Urine	*

* - For sampling details, please see the source document.

Exposure Guidelines

US - California OELs: Skin designation

Propylene Glycol Monomethyl Ether Acetate (108-65-6) Can be absorbed through the skin.

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Wear safety glasses with side shields (or goggles).

Hand Protection: Wear appropriate chemical resistant gloves.

Skin Protection

Other: Wear suitable protective clothing.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical and Chemical Properties

Appearance	Flash Point: -2.0 °F (-18.9 °C) estimated	Relative Density: Not available.
Physical State: Gas.	Evaporation Rate: > 1 BuAc estimated	Solubility(ies)
Form: Aerosol. Liquefied gas.	Flammability (solid, gas) Not available.	Solubility (water): Not available.
Color: Not available.	Upper/Lower Flammability or Explosive Limits	Auto-Ignition Temperature: Not available.
Odor: Not available.	Explosive Limit - Lower (%) : 1.7 estimated	Decomposition Temperature: Not available.
Odor Threshold: Not available.	Explosive Limit - Upper (%) : 10.9 estimated	Viscosity: Not available.
pH: Not available.	Vapor Pressure: 40 psig @70F estimated	Other Information

Melting Point/Freezing Point: Not available.

Vapor Density: Not available.

Specific Gravity: 0.81 estimated

Initial Boiling Point and Boiling Range: -47.2 °F (-44 °C) estimated

Section 10 ~ Stability and Reactivity**Reactivity:** The product is stable and non-reactive under normal conditions of use, storage and transport.**Chemical Stability:** Material is stable under normal conditions.**Possibility of Hazardous Reactions:** Hazardous polymerization does not occur.**Conditions to Avoid:** Avoid temperatures exceeding the flash point. Contact with incompatible materials.**Incompatible Materials:** Strong acids. Strong oxidizing agents. Nitrates. Aluminum. Halogens. Phosphorus. Fluorine. Chlorine.**Hazardous Decomposition Products:** No hazardous decomposition products are known.**Section 11 ~ Toxicological Information****Information on Likely Routes of Exposure****Ingestion:** Expected to be a low ingestion hazard.**Inhalation:** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.**Skin Contact:** No adverse effects due to skin contact are expected.**Eye Contact:** Causes serious eye irritation.**Symptoms Related to the Physical, Chemical and Toxicological Characteristics:** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.**Information on Toxicological Effects****Acute Toxicity:** Narcotic effects.

<i>Components</i>	<i>Species</i>	<i>Test Results</i>
Acetone (67-64-1)		
Acute		
Dermal LD50	Guinea pig	>7426 mg/kg, 24 Hours
	Rabbit	>9.4 ml/kg, 24 Hours
		>7426 mg/kg, 24 Hours
		>9.4 ml/kg, 24 Hours
Inhalation LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral LD50	Rat	5800 mg/kg
		2.2 ml/kg
Barium Sulfate, Natural (7727-43-7)		
Acute		
Oral LD100	Rat	564 g/kg
LD50	Rat	307 g/kg
Butane (106-97-8)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
		52%, 120 Minutes
	Rat	1355 mg/l
Ethylene Glycol Propyl Ether (2807-30-9)		
Acute		
Dermal LD50	Guinea pig	5.6 g/kg, 4 Days
	Rabbit	> 1 g/kg, 24 Hours
		1337 ml/kg, 14 Days
Inhalation LC50	Rat	>2132 ppm, 6 Hours
		>1800 ppm
Oral LD50	Guinea pig	2.2 g/kg
	Mouse	1774 mg/kg
	Rat	0.5 – 1 g/kg
Isobutyl Acetate (110-19-0)		
Acute		
Dermal LD50	Rabbit	> 17400 mg/kg, 24 Hours
	Rat	5000 mg/kg
Inhalation LC50	Rat	> 30 mg/l, 6 Hours
		>23.4 mg/l, 4 Hours
Oral LD50	Rat	13413 mg/kg
Methyl Isobutyl Ketone (108-10-1)		
Acute		
Inhalation LC50	Rat	2000 – 4000 ppm, 4 Hours
Oral LD50	Rat	2.08 g/kg
Propane (74-98-6)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
		52%, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Propylene Glycol Monomethyl Ether Acetate (108-65-6)		
Acute		
Dermal LD50	Rat	>2000 mg/kg, 24 Hours
Oral LD50	Rat	>14.1 ml
		5155 mg/kg
Titanium Dioxide (13463-67-7)		
Acute		
Inhalation LC50	Rat	>2.28 mg/l, 4 Hours
Oral LD50	Rat	>11000 mg/kg
Xylene (1330-20-7)		
Acute		
Dermal LD50	Rabbit	>5000 ml/kg, 4 Hours
		12126 mg/kg, 24 Hours
Inhalation LC50	Rat	5922 ppm, 4 Hours
Oral LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg
		10 ml/kg

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Prolonged skin contact may cause temporary irritation.**Serious Eye Damage/Eye Irritation:** Causes serious eye irritation.**Respiratory or Skin Sensitization****Respiratory Sensitization:** Not available.**Skin Sensitization:** This product is not expected to cause skin sensitization.**Germ Cell Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl Isobutyl Ketone (108-10-1) 2B Possibly carcinogenic to humans.
Titanium dioxide (13463-67-7) 2B Possibly carcinogenic to humans.
Xylene (1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Reproductive Toxicity: Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific Target Organ Toxicity - Single Exposure: May cause drowsiness and dizziness.

Specific Target Organ Toxicity - Repeated Exposure: Not classified.

Aspiration Hazard: Not likely, due to the form of the product.

Chronic Effects: Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Section 12 ~ Ecological Information

Ecotoxicity: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Acetone (67-64-1) Aquatic Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
Barium Sulfate, Natural (7727-43-7) Aquatic Crustacea	EC50	Tubificid worm (Tubifex tubifex)
Isobutyl Acetate (110-19-0) Aquatic Fish	LC50	Fish
Methyl Isobutyl Ketone (108-10-1) Aquatic Fish	LC50	Fathead minnow (Pimephales promelas)
Methyl Propyl Ketone (107-87-9) Aquatic Fish	LC50	Fathead minnow (Pimephales promelas)
Propylene Glycol Monomethyl Ether Acetate (108-65-6) Aquatic Crustacea	EC50	Daphnia
Titanium Dioxide (13463-67-7) Aquatic Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Mummichog (Fundulus heteroclitus)
Xylene (1330-20-7) Aquatic Fish	LC50	Bluegill (Lepomis macrochirus)

* Estimates for product may be based on additional component data not shown.

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential: No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24	Butane	2.89	Isobutyl Acetate	1.78	Methyl Isobutyl Ketone	1.31	Methyl Propyl Ketone	0.91
Propane	2.36	Xylene	3.12 - 3.2						

Mobility in Soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal Instructions: Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations: Dispose in accordance with all applicable regulations.

Hazardous Waste Code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (67-64-1) U002
Methyl Isobutyl Ketone (108-10-1) U161
Xylene (1330-20-7) U239

Waste from Residues / Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

Section 14 ~ Transportation Information

DOT	IATA	IMDG
UN Number: UN1950	UN Number: UN1950	UN Number: UN1950
UN Proper Shipping Name: Aerosols, flammable	UN Proper Shipping Name: Aerosols, flammable	UN Proper Shipping Name: AEROSOLS
Transport Hazard Class(es)	Transport Hazard Class(es)	Transport Hazard Class(es)
Class 2.1	Class: 2.1	Class: 2.1
Subsidiary Risk -	Subsidiary Risk -	Subsidiary Risk -
Label(s): 2.1	Label(s): 2.1	Label(s): 2.1
Packing Group: Not applicable.	Packing Group: Not applicable.	Packing Group: Not applicable.
Special Provisions: N82	Environmental Hazards: No.	Environmental Hazards
Packaging Exceptions: 306	ERG Code: 10L	Marine Pollutant: No.
Packaging Non Bulk: None	Passenger and Cargo Aircraft: Allowed.	EmS: F-D, S-U
Packaging Bulk: None	Other Information	Packaging Exceptions: LTD QTY
	Cargo Aircraft Only: Allowed.	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.
	Packaging Exceptions: LTD QTY	

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

DOT

IATA;IMDG



Section 15 ~ Regulatory Information

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (67-64-1) Listed. Isobutyl Acetate (110-19-0) Listed. Methyl Isobutyl Ketone (108-10-1) Listed. Xylene (1330-20-7) Listed.

SARA 304 Emergency Release Notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories: Immediate Hazard – Yes Delayed Hazard – No Fire Hazard – Yes Pressure Hazard – Yes Reactivity Hazard – No

SARA 302 Extremely Hazardous Substance: Not listed.

SARA 311/312 Hazardous Chemical: No

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.
Methyl Isobutyl Ketone	108-10-1	2.5 – 10
Xylene	1330-20-7	1 – 2.5

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methyl Isobutyl Ketone (108-10-1) Xylene (1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (106-97-8) Propane (74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA), List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (67-64-1) 6532 Methyl Isobutyl Ketone (108-10-1) 6715

Drug Enforcement Administration (DEA), List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (67-64-1) 35 %WV Methyl Isobutyl Ketone (108-10-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (67-64-1) 6532 Methyl Isobutyl Ketone (108-10-1) 6715

US State Regulations

US, Massachusetts RTK - Substance List	US, New Jersey Worker and Community Right-to-Know Act	US, Pennsylvania Worker and Community Right-to-Know Law	US, Rhode Island RTK
Acetone (67-64-1)	Acetone (67-64-1)	Acetone (67-64-1)	Acetone (67-64-1)
Barium Sulfate, Natural (7727-43-7)	Barium Sulfate, Natural (7727-43-7)	Barium Sulfate, Natural (7727-43-7)	Butane (106-97-8)
Butane (106-97-8)	Butane (106-97-8)	Butane (106-97-8)	Isobutyl Acetate (110-19-0)
Isobutyl Acetate (110-19-0)	Isobutyl Acetate (110-19-0)	Isobutyl Acetate (110-19-0)	Methyl Isobutyl Ketone (108-10-1)
Methyl Isobutyl Ketone (108-10-1)	Methyl Isobutyl Ketone (108-10-1)	Methyl Isobutyl Ketone (108-10-1)	Propane (74-98-6)
Methyl Propyl Ketone (107-87-9)	Methyl Propyl Ketone (107-87-9)	Methyl Propyl Ketone (107-87-9)	Xylene (1330-20-7)
Propane (74-98-6)	Propane (74-98-6)	Propane (74-98-6)	
Titanium dioxide (13463-67-7)	Titanium dioxide (13463-67-7)	Titanium dioxide (13463-67-7)	
Xylene (1330-20-7)	Xylene (1330-20-7)	Xylene (1330-20-7)	

US, California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methyl Isobutyl Ketone (108-10-1) Listed: November 4, 2011 Titanium dioxide (13463-67-7) Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCs)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	2	2*	4= Severe
FLAMMABILITY	4	4	3= Serious
REACTIVITY	2	2	2= Moderate
OTHER/PROTECTION	-	X	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.