

Foamy Lube



Foaming Chain and Cable Lubricant



FOAMY LUBE sprays as an instant foaming, deep penetrating liquid that flows inside intricate chains and cables where the greatest stress occurs. **FOAMY LUBE** provides a thick foam that clings to vertical surfaces. As foam breaks, lubricant penetrates into wire rope, rollers, pins, links and bushings of chains. Leaves a lubricating film, which reduces friction, wear and corrosion. When applied to wire ropes and cables, the *Moly and other additives plate the strands to provide anti-wear and rust protection. (*Moly is molybdenum disulfide).

DIRECTIONS: SHAKE WELL. Make the can rattle 1 minute before using. For proper spraying, can should be near room temperature (about 72°F / 22°C). Parts to be sprayed should be reasonably clean and dry. Spray, holding can 8 to 10 inches from point to be lubricated. Make sure arrow on spray tip points away. For point lubrication, use plastic extension tube, insert into nozzle for reaching places where a spray pattern is not desired. Spray may be applied holding can upside down, sideways, right side up...in almost any position. If spray tip should close, remove and clean in solvent.

Areas of Use:

- *Shipyards
- *Industrial facilities
- *Steel mills
- *Aircraft maintenance
- *Road equipment
- *Construction mining
- *Chains and cables
- *Tow lines
- *Hoists and winches
- *Material handling
- *Open gears
- *Sprocket
- *Chainsaws
- *Power drives
- *Drag lines
- *Cranes
- *Linkages and roller assemblies

Health	*3
Flammability	4
Physical Hazard	3
Protection	B

Appearance and Odor.....	Liquid, odor not available.
VOC.....	20.00000%
Net Wt.....	16 oz.

Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134