

GREASE SLAYER



Sewer Line Cleaner and Degreaser

GREASE SLAYER is a non-freezing emulsifying agent and odor control product for sewer lines. Designed to liquify fats, oils and grease in sewer lines, open leaching beds, clean drain lines, cesspools, grease traps and septic tanks. **GREASE SLAYER** provides a powerful odor blanket for use in eliminating offensive odors in garbage dumps, trash cans, lift stations, and sewage plants. **GREASE SLAYER** contains no phosphates, no quaternary compounds and no chlorinated solvents. Contains no alkalis or acids. Will not inhibit waste digestion or affect B.O.D. or O.D.I. when used as directed.



DIRECTIONS

LIFT STATIONS:

1. Turn on manual operation.
2. Pump completely down.
3. Add 20 gallons of degreaser for every 50 gallons of lift station capacity.
4. Let rise to maximum height.
5. Turn automatic operation back on.

DIGESTERS:

1. Add 20 gallons of degreaser for each foot of scum and allow to sit for 20 minutes.
2. Add 60 gallons of water and allow to sit for an additional 20 minutes.
3. Agitate or re-circulate digester.

Health	2
Flammability	1
Physical Hazard	0
Protection	B

Areas of Use:

- *Municipalities
- *Water Treatment Plants
- *Cities & Counties

Appearance & Odor.....	Blue liquid with characterestic odor.
Net Contents.....	5 Gal.

Omega Industrial Supply, Inc.

Fairfield, CA 94534
1-800-571-7347 www.onlyomega.com Fax: 707-864-8134