

Section 1 ~ Identification

Identity (As Used On Label and List) A1048 ACOUSTA TILE	Date Prepared: 10/29/24
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-255-3924
Address (Number, Street, Suite/Apt#) 1133 WEST 27 TH STREET	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) CHEYENNE, WY 82001	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Classifications	Flammable Aerosol: Category 1 Gases Under Pressure: Liquefied Gas Skin Irritant: Category 2 Eye Irritant: Category 2A Specific Target Organ Toxicity (Single Exposure): Category 3 Aspiration Hazard: Category 1
------------------------	---

Label Elements



Signal Word: DANGER

Hazard Statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. May be fatal if swallowed and enters airways.

Precautionary Statement

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well ventilated area. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Get emergency medical help immediately. Do NOT induce vomiting. Store in a well ventilated place. Dispose of contents and container in accordance with local, state and federal regulations.

Other Hazards

N/A

Unknown acute toxicity (GHS US)

0%

Section 3 ~ Composition/Information on Ingredients

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Propane/n-Butane	68476-86-8	15-40%
Acetone	67-64-1	10-30%
Heptane	142-82-5	10-30%
Ethyl alcohol	64-17-5	5-10%
Distillates (petroleum), hydrotreated light	64742-47-8	3-7%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration.

Seek medical attention if irritation persists.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision. Skin: defatting and dermatitis. Inhalation: Anesthetic, irritation, Central Nervous System depression.

Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

CHRONIC HEALTH HAZARDS: May be toxic to kidneys and liver.

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed toward the control of symptoms and the clinical condition of the patient.

Section 5 ~ Firefighting Measures

EXTINGUISHING MEDIA: Dry chemical or suitable for surrounding materials.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure to temperatures above 120 °F may cause bursting. Keep away from sparks, open flames and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, hydrocarbons.

Section 6 ~ Accidental Release Measures

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Wipe up small spill with towel and allow area to dry. excess may be removed after drying with sandpaper or other scraping device. dispose of residue in accordance with federal, state and local guidelines.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered Non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261). Solvent is flammable please refer to (40 CFR 261).

Section 7 ~ Handling and Storage

HANDLING AND STORAGE: Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well ventilated area.

Do not expose to temperatures exceeding 50 °C/122 °F.

OTHER PRECAUTIONS: Keep out of the reach of children. Follow label directions exactly. Vapors may collect in low lying areas.

INCOMPATIBILITY: Some plastics and painted surfaces, pre-test before using.

Section 8 ~ Exposure Controls/Personal Protection

HAZARDOUS INGREDIENT

<u>HAZARDOUS INGREDIENT</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Acetone	1000 ppm	500 ppm
Ethyl alcohol	1000 ppm	1000 ppm
Heptane	Not Established	400 ppm
Distillates (petroleum), hydrotreated light	400 ppm	400 ppm
Propane/n-Butane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: Ambient ventilation suitable, forced ventilation should not be required.

RESPIRATORY PROTECTION: Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles and chemical resistant gloves.

ADDITIONAL MEASURES: Wash hands and all equipment thoroughly after use.

Section 9 ~ Physical and Chemical Properties

APPEARANCE: White, Opaque Spray

ODOR: Hydrocarbon.

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: N/D

FLAMMABILITY (solid/gas): Extremely flammable aerosol.

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOSIVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): N/A

VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H₂O=1): 0.821-0.93

SOLUBILITY(IES): Negligible.

PARTITION COEFFICIENT: n-OCTANOL/WATER (KOW): N/D

AUTOIGNITION TEMPERATURE: N/D

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: N/D

Section 10 ~ Stability and Reactivity

REACTIVITY: None known.

CHEMICAL STABILITY: Stable.

POSSIBLE HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Temperatures greater than 122 °F (50 °C) and sources of ignition.

INCOMPATIBLE MATERIALS: Some plastics and painted surfaces, pre-test before using.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

Section 11 ~ Toxicological Information

TOXICOLOGICAL INFORMATION: Acetone (67-64-1): LD50 (Oral, Rat) 5800 mg/kg; LD50 (Oral, Mouse) 3000 mg/kg; LD50 (Oral, Rabbit) 5340 mg/kg;

LC50 (Inhalation, Rat, 8h) 50100 mg/m³; LC50 (Inhalation, Mouse, 4h) 44,000 mg/m³. Ethyl alcohol (64-17-5): LC50 (Inhalation, Rat, 4h) 133.6 mg/L;

LD50 (Oral, Rat) > 8311 mg/kg; LD50 (Dermal, Rabbit) 16972.5 mg/kg. Heptane(142-82-5): LD50 (Oral, Rat) > 15000 mg/kg; LD50 (Dermal, Rabbit) > 3160 mg/kg;

LC50 (Inhalation, Rat, 4h) 103 mg/L. Isoparaffinic Hydrocarbon (64742-47-8): LD50 (Oral, Rat) > 5000 mg/kg; LD50 (Dermal, Rabbit) > 2000 mg/kg.

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation, defatting.

INGESTION: Causes gastrointestinal irritation, nausea, diarrhea. Absorption through gastrointestinal tract may produce symptoms of central nervous system depression ranging from light headedness to unconsciousness.

INHALATION: Causes dizziness, headaches, nausea, central nervous system (CNS) depression. Excessive or prolonged exposure may cause unconsciousness.

SKIN: Causes localized defatting, irritation, dermatitis.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.
ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision. Skin: defatting and dermatitis. Inhalation: Anesthetic, irritation, Central Nervous System depression.
Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk
CHRONIC HEALTH HAZARDS: May be toxic to kidneys and liver.
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

Section 12 ~ Ecological Information

ECOTOXICITY: **Acetone** (67-64-1): LC50 (Oncorhynchus mykiss, 96h) 5540 mg/L; EC50 (Daphnia magna, 48h) 6100 mg/L; EC50 (Selenastrum quadricauda, 8d) 7500 mg/L; EC50 (Pseudomonas putida, 16h) 1700 mg/L. **Isoparaffinic Hydrocarbon** (64742-47-8) Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility. May adsorb to sediments and possibly cause toxic effects to organisms. **Ethyl alcohol** (64-17-5): LC50 (Fish, 96h) 12,900 - 15,300 mg/L; LC50 (Bacteria, 24h) 11,200 mg/L; EC50 (Bacteria, 5 - 30m) 34,900 mg/L. **Heptane** (142-82-5): EC50 (Daphnia magna, 48h) 1.50 mg/L.
PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.
BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.
MOBILITY IN SOIL: This product is mobile in soil.
OTHER ADVERSE EFFECTS: This material is toxic to aquatic life.

Section 13 ~ Disposal Considerations

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.
RCRA STATUS: Waste likely considered Non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261). Solvent is flammable please refer to (40 CFR 261).

Section 14 ~ Transportation Information

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950
PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Flammable.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950
PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)
PROPER SHIPPING NAME: Aerosols.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950
PACKING GROUP: N/A
ENVIRONMENTAL HAZARDS WATER: Marine Pollutant.

Section 15 ~ Regulatory Information

TSCA STATUS: All chemicals are listed or exempt.
CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): **Acetone** (67-64-1) Reportable Quantity = 5,000 pounds.
SARA 311/312 HAZARD CATEGORIES: Health Hazard and Physical Hazard.
SARA 313 REPORTABLE INGREDIENTS: **Ethyl Alcohol** (64-17-5) acute, chronic, flammable.
STATE REGULATIONS: **Acetone** (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA. **Heptane** (142-82-5): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, IL, MA, NJ, PA, RI. **Ethyl Alcohol** (64-17-5): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, ID, MA, MN, NJ, PA, WA. **Propane** (74-98-6): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CT, DE, MA, MN, NJ, PA.
INTERNATIONAL REGULATIONS: **Acetone** (67-64-1) Australia, Japan, Korea, United Kingdom, Canada, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC). p. 6; DSCL (EEC): R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16- Keep away from ignition sources. S26- In case of eye contact, rinse immediately with plenty of water and seek medical advice.
VOLATILE ORGANIC COMPOUNDS (VOC): 51%

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	2	2	4= Severe
FLAMMABILITY	2	2	3= Serious
REACTIVITY	0	0	2= Moderate
PROTECTIVE EQUIPMENT		B	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and -may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.