





This brief provides a general overview of the **Safety Data Sheet** requirements in the Hazard Communication Standard OSHA's 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200).

Section 1 ~ Identification

Identity (As Used On Label and List) A1156 FACE LIFT FOR ASPHALT	Date Prepared: 03/08/2023
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 1133 WEST 27TH STREET	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) CHEYENNE, WY 82001	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

<i>Classifications</i>	Flam. Aerosol 1 Press. Gas Eye Irrit. 2A STOT RE 1	H222 H280 H319 H372	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes damage to the central nervous system through prolonged or repeated exposure		
<i>Label elements</i>	 GHS02	 GHS04	 GHS08	 GHS07	Signal Word: Danger
<i>Hazard Statement</i>	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes damage to the central nervous system through prolonged or repeated exposure.				
<i>Precautionary Statement Prevention</i>	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fumes/gas/mist/vapors/spray. If in Eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention. Protect from sunlight.				
<i>Storage</i>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.				
<i>Disposal</i>	Dispose of contents/container in accordance with local/regional/national/international regulations.				

Section 3 ~ Composition/Information on Ingredients

Dangerous Components:	CAS No.	%(Wt.)
VM&P Naphtha	64742-89-8	37.62%
Dimethyl Ether	115-10-6	24.99%
Calcium Carbonate	1317-65-3	17.19%
Asphalt	8052-42-4	11.93%
Silicon Dioxide	112926-00-8	2.29%
Stoddard Solvent	8052-41-3	2.07%
Chemical characterization: Mixtures		
Chemical Description: This product is a mixture of the substances listed above with nonhazardous additions.		

Section 4 ~ First Aid Measures

After Inhalation — Supply fresh air; consult doctor in case of complaints.
After Skin Contact — Remove contaminated clothing. Wash exposed area with soap and water.
After Eye Contact — Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After Swallowing — Rinse out mouth and then drink plenty of water. Rinse mouth out with water. Do not induce vomiting.
Most Important Symptoms/Effects — Dizziness
Indication of Immediate Medical Attention Needed — No further relevant information available.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Specific Hazards: Can form explosive gas-air mixtures
Special Equipment for Firefighters: A respiratory protective device may be necessary.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and Materials for Containment and Cleaning Up: Absorb liquid components with liquid-binding material.

Section 7 ~ Handling and Storage

Precautions for safe handling storage requirements — Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

Section 8 ~ Exposure Controls/Personal Protection

Components with limit values that require monitoring at the workplace:

Components	Type	Value	Components	Type	Value
115-10-6 Dimethyl Ether	WEEL (USA)	Long-term value: 1000 ppm	112926-00-8 Silicon Dioxide	PEL (USA)	20mppcf or 80mg/m ³ %SiO ₂
8052-42-4 Asphalt	REL (USA)	Ceiling limit value: 5* mg/m ³ *15-min; See Pocket Guide App. A		REL (USA)	Long-term value: 6 mg/m ³ See Pocket Guide App. C
	TLV (USA)	Long-term value: 0.5* mg/m ³ *inh. fraction; as benzene-soluble aerosol; BEIp		TLV (USA)	TLV withdrawn
Ingredients with biological limit values:			8052-41-3 Stoddard Solvent	PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm
8052-42-4 Asphalt	BEI (USA)	<i>Medium:</i> Urine <i>Time:</i> End of shift at end of workweek <i>Parameter:</i> 1-Hydroxypyrene with hydrolysis (nonquantitative)		REL (USA)	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
			TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm	

Breathing Equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand Protection: Nitrile gloves. Protective gloves. The glove material must be impermeable and resistant to the substance

Hygienic Protection: Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

Eye Protection: Tightly sealed goggles

Section 9 ~ Physical Chemical Properties

Appearance and Odor:	Aerosol, aromatic.	Vapor Pressure	Not Determined.
pH	Not Determined.	Relative Density	Between 0.77 and 0.85 (Water equals 1.00)

Melting/Freezing Point	Undetermined	Vapor Density	Not Determined.
Boiling Point	-24 °C (-11 °F)	Evaporation Rate	Not Applicable.
Flash Point	-19 °C (-2°F)	Partition coefficient: n-octanol/water	Not Determined.
Flammability (solid, gas)	Extremely flammable.	Solubility	Not Determined.
Decomposition Temperature	Not Determined.	Viscosity	Not Determined.
Auto - Ignition	Product is not self-igniting	VOC Content	576.9 g/l / 4.81 lb/gl
Danger of explosion	In use, may form flammable/explosive vapor-air mixture.	VOC Content (less exempt solvents)	65.4%
Lower Explosion Level	3.0 Vol %	MIR Value	0.77
Upper Explosion Level	18.6 Vol %	Solids Content	34.5%

Section 10 ~ Stability and Reactivity

Chemical Stability: Not fully evaluated	Possibility of Hazardous Reactions: No dangerous reactions known.
Incompatibility Materials: No further relevant information available.	Hazardous Decomposition: No dangerous decomposition products known.
Reactivity: Stable at normal temperatures.	Conditions to Avoid: No decomposition if used according to specifications.

Section 11 ~ Toxicological Information

LD/LC50 values that are relevant for classification:
115-10-6
Inhalative LC50/4 h 308 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic Categories

IARC (International Agency for Research on Cancer)
8052-42-4 Asphalt 2B
NTP (National Toxicology Program)
None of the ingredients is listed.

Section 12 ~ Ecological Information

Aquatic Toxicity: Hazardous for water, do not empty into drains.
Persistence and Degradability: The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative Potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other Adverse Effects: No further relevant information available.

Section 13 ~ Disposal Considerations

Dispose of in accordance with local, State, and Federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

Section 14 ~ Transport Information

US Dept. of Transportation (DOT)		Special precautions for user:	Warning: Gases
Proper Shipping Name:	Consumer Commodity ORM-D Aerosols, flammable	Marine pollutant:	No
Hazard Class:	2.1	EMS Number:	F-D, S-U
UN Number:	UN1950	UN "Model Regulation":	UN1950, Aerosols, 2.1
ADR:	1950 Aerosols		

Section 15 ~ Regulatory Information

SARA Section 355 (extremely hazardous substances): None of the ingredients in this product are listed.
SARA Section 313 (Specific toxic chemical listings): None of the ingredients is listed.
CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemicals known to cause cancer: 1333-86-4 Carbon black, 100-41-4 ethyl benzene
Canadian Environmental Protection Act: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.
WHIMS Symbols for Canada: A- Compressed gas. D2B – Toxic material causing other toxic effect.



EPA: None of the ingredients is listed.

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	1	1	4= Severe
FLAMMABILITY	4	3	3= Serious
REACTIVITY	3	3	2= Moderate
OTHER/PROTECTION	-	B	1= Slight 0= Minimal

Disclaimer: This product was manufactured in the U.S.A. The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.