

Section 1 ~ Identification

Identity (As Used On Label and List) MM5061 MEGA SHOT	Date Prepared: 01/10/20
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 1133 WEST 27 TH STREET	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) CHEYENNE, WY 82001	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Classifications Physical Hazards - Flammable Aerosols - Category 2. Gases Under Pressure - Liquefied Gas.
Health Hazards - Not Classified.
Environmental Hazards - Not Classified.

Label Elements



Signal Word: WARNING

Hazard Statement H223:Flammable aerosol. H280:Contains gas under pressure; may explode if heated (L).

Precautionary Statement

Prevention - P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use.
Response - None .
Storage - P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403:Store in a well ventilated place .
Disposal - None.

Other Hazards

None Known

Section 3 ~ Composition/Information on Ingredients

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
1,1-Difluoroethane	75-37-6	80-100
Acetone	67-64-1	0.1-1

Section 4 ~ First Aid Measures

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.

Skin Contact: Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.

Eye Contact: Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.

Ingestion: Ingestion is unlikely to occur. If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention.

Most important symptoms/effects, acute and delayed: Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

Indication of immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Section 5 ~ Firefighting Measures

General Fire Hazards: Flammable.

Suitable Extinguishing Media: Dry chemical powder. Carbon dioxide. Foam, water spray or fog.

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical: In case of fire, the following can be released: Carbon Oxides (CO, CO₂), Other unidentified Organic Compounds.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

Methods and Materials for Containment and Cleaning Up: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Section 7 ~ Handling and Storage

Precautions for Safe Handling: Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.

Conditions for Safe Storage including any Incompatibilities: Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

Section 8 ~ Exposure Controls/Personal Protection

INGREDIENTS	ACGIH TLV		OSHA PEL	STEL	NIOSH REL
	TWA	STEL			
1,1-Difluoroethane	Not available	Not available	Not available	Not available	Not available
Acetone	250 ppm	500 ppm	1,000 ppm (2,400mg/m ³)	Not available	Not available

Appropriate Engineering Controls: Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.

Individual Protection Measures

Eye/Face Protection: Chemical splash goggles are recommended.

Skin Protection: Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.

Respiratory Protection: Use approved NIOSH respirators for emergencies.

Thermal Hazards: None Known.

General Hygiene Considerations: When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

Section 9 ~ Physical and Chemical Properties

Form: Gas.

Physical Appearance: Clear/Transparent . Colorless gas.

Odor: Ether odor.

Odor Threshold (ppm): N/A.

Aerosol Vapour Pressure (psig, 21°C): 80-95.

Specific Gravity: 0.875-0.915.

Vapour Density (Air=1): 2.4.

pH: N/A.

Boiling Point (°C): -25.

Freezing Point (°C): -117.22 °C (-179 °F).

Flash Point (°C), Method: < . -50.

Flashback: N/A.

Evaporation Rate (n-Butyl Acetate = 1): Not available.

VOC Content: 0%.

Solubility in water: 0.28 wt.% @25°C.

Auto Ignition Temperature (°C): Not available.

Aerosol Flame Projection: N/A.

Lower Flammable Limit (% Vol): 3.9.

Upper Flammable Limit (% Vol): 16.9.

Partition Coefficient (n-Octanol/Water): 1.13.

Viscosity: N/A.

Section 10 ~ Stability and Reactivity

Reactivity: Product not reactive under normal conditions of use.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Will not occur.

Conditions to Avoid: Avoid sources of heat and flame, and electrostatic charge.

Incompatible Materials: Keep away from heat. Strong oxidizing agents.

Hazardous Decomposition Products: See Section 05.

Section 11 ~ Toxicological Information

INGREDIENTS	LC50	LD50
1,1-Difluoroethane	176 mg/L (Rat - 4 hrs)	Not available
Acetone	71 mg/L (Rat - 4 hrs)	5,800 mg/kg (Oral - Rat); >15,800 mg/kg (Dermal - Rabbit)

Information on Likely Routes of Exposure

Routes of entry – Inhalation: Prolonged inhalation may be harmful.

Routes of entry - Skin & Eye: Contact with liquid may cause frostbite.

Routes of entry – Ingestion: No.

Routes of entry - Skin Absorption: No.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics

Acute Toxicity: Inhalation: Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolong inhalation may be harmful.

Skin Corrosion/Irritation: N/A.

Serious Eye Damage/Eye Irritation: N/A.

Respiratory or Skin Sensitization: N/A.

Germ Cell Mutagenicity: No information is available, and no adverse effects are expected.

Carcinogenicity: None of the ingredients are listed as possibly carcinogenic to humans by IARC or ACGIH.

Reproductive Toxicity: No information is available.

STOT - Single Exposure: Not classified.

STOT - Repeated Exposure: Not classified.

Aspiration Hazard: Not classified.

Chronic Effects: May cause damage to the Central Nervous System through prolonged or repeated exposure. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness.

Section 12 ~ Ecological Information

Ecotoxicity: May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment.

Persistence and degradability: The product itself has not been tested.

Bioaccumulation Potential: The product itself has not been tested.

Mobility in Soil: The product itself has not been tested.

Other Adverse Effects: None Known.

Section 13 ~ Disposal Considerations

Appropriate Disposal Methods: This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

Section 14 ~ Transportation Information

TDG (Canada- Road): UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

IMDG (International- Marine): UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

IATA (International- Air): UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

DOT (US-Road): UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.

Section 15 ~ Regulatory Information

Canada Regulations: Refer to Section 2 for a WHMIS 2015 Classification for this product.

Canadian Environmental Protection Act (CEPA): All ingredients listed appear on the Domestic Substances List (DSL).

US Regulations

TSCA Inventory Status: All components are listed on TSCA.

OSHA: This product is considered hazardous under the Federal OSHA hazard communication standard.

California Proposition 65: This product does not contain any chemical(s) known to the state of California to cause cancer or reproductivity toxicity.

Section 16 ~ Other Information

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and -may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet