

Super C

Industrial Caulk and Sealant



SUPER C is a highly adhesive clear sealer that is designed to seal siding, ducts, vents, gutters, windows, doors and anywhere else that needs a watertight and weatherproof seal. It remains flexible, weather resistant, crack free and resists yellowing. Tack free in less than 20 minutes. Paintable after 24 hours with high-quality latex paint only. **SUPER C** will adhere to vinyl, aluminum, wood, glass, tile, metal, masonry, brick, concrete and drywall/plaster. Service temperature range (cured sealant) is -35°F to 350°F. Temperature application range is 20°F to 140°F.

DIRECTIONS: Remove any old sealant and any loose dirt or debris. Trim nozzle to desired bead size and angle, then puncture inner seal and load into caulking gun. Fill cracks and holes with sealant, then smooth with tool and clean up excess immediately with mineral spirits.

FOR BEST RESULTS: Clean area with Omega's **Mega Power** degreaser to remove any grease or oily residue for best adhesion. Do not apply when temperatures are below 20°F, or when raining or freezing temperatures are eminent. Store away from extreme temperatures. Do not use on polystyrene products, when using on other plastics, test first for compatibility. Not recommended for underwater or below grade, on stovepipes, chimneys, fireplace applications, tuck-pointing, or surface defects. Joint width/depth should not exceed 1/2". Allow to 5-7 days for sealant to cure, depending upon size of bead. **SUPER C** will not cure in totally confined spaces.

| | |
|-----------------|---|
| Health | 1 |
| Flammability | 2 |
| Physical Hazard | 1 |
| Protection | X |

Areas of Use:

- *Hotels
- *Hospitals
- *School Busses
- *Apartment Complexes
- *Cities and Counties
- *Amusement Parks
- *Industrial Facilities
- *Plumbing Departments
- *Paint Departments

| | |
|--------------------------|----------------------------|
| Appearance and odor..... | Clear paste, Solvent odor. |
| Specific Gravity..... | N/A |
| VOC | 17% |
| NFPA Fire Rating | Flammable |

Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134