

# Super Silicone



Dry Silicone Spray  
Food Grade



**SUPER SILICONE** is designed to lubricate equipment used in the packaging and processing industry. Leaves a non-staining dry pure silicone film to lubricate moving parts, reducing friction and wear. Product is heat stable from -35°F to 350°F. Also formulated as a release agent on seals and gaskets of tank closures. Lubricates all sliding surfaces except those you wish to paint. Excellent on RV slide outs. Use on sticking metal, wood, rubber and plastic. Apply to cutting tables, conveyors, heat sealing equipment and slicing equipment. Waterproofs leather, canvas, rubber and chrome surfaces. Safe on all plastics. Contains no methylene chloride. Won't melt, freeze, gum or become rancid.

**DIRECTIONS:** Read cautions and directions carefully before use. Area to be lubricated should be clean and dry. Shake well before use. Hold can 6-8 inches from surface. Spray in short bursts. Spray no more than required to lubricate surface. Do not spray electrical equipment while in use. Wait 5-10 minutes before operating electrical equipment after using. Spray is dry. Do not expect a liquid. Used as directed, it will not harm most surfaces.

|                 |   |
|-----------------|---|
| Health          | 1 |
| Flammability    | 3 |
| Physical Hazard | 0 |
| Protection      | B |

**Areas of Use:**

- \*Conveyors
- \*Food Processing Equipment
- \*Parks/Recreations
- \*Hotels
- \*Hinges, locks and handles
- \*School Districts
- \*Amusement Parks
- \*Restaurants

|                          |                                |
|--------------------------|--------------------------------|
| Appearance and odor..... | Clear spray with solvent odor. |
| Specific Gravity.....    | 0.755                          |
| VOC % .....              | 55%                            |
| Net Wt. ....             | 11.5 oz.                       |

***Omega Industrial Supply, Inc.***

Fairfield, CA 94534  
1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134