

ARMOR COAT

Stainless Steel Flakes
with a Polyurethane Binder



ARMOR COAT has a super tough long-lasting coat containing 100% pure 316L stainless steel pigment in an ultra durable resin system, heat resistant up to 250°F and rust protection. Seals, beautifies and protects metal, wood, ceramics and more. **ARMOR COAT** helps prevent deterioration caused by harsh chemicals, severe atmospheres or conditions. Tack free in 5 minutes, hard cure in 2 hours.

DIRECTIONS:

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C.).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. **DO NOT** incinerate or compact.

Areas of Use:

- *Factories
- *Cities & Counties
- *Hotels
- *Restaurants & Bars
- *Schools
- *Mechanic Shops
- *HVAC Companies
- *Food Processing Plants

Appearance & Odor.....	Aerosol with aromatic odor
Relative Density.....	Between 0.77 and 0.85 (Water equals 1.00)
Net Contents.....	13 OZ. (369 Grams)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631