

CT FLUID

Cutting & Tapping Fluid



CT FLUID is a foaming transparent coolant and lubricant designed for portable and field operations. **CT FLUID** is useful on many surfaces including Carbon Steel, Stainless Steel, Aluminum, Bronze, Titanium, Chrome-Moly, Vanadium Steel, Inconel, Monel, Phosphor, Beryllium-Copper and other exotic alloys. **CT FLUID** cools work pieces, causing less heat distortion and tool burning, thereby increasing production and lengthening tool life. **CT FLUID** is transparent providing better visibility of work area, its foam clings to cutting tools therefore reducing waste and over spray and cooling cutting tools for a longer tool life.

DIRECTIONS:

Shake can well before using. Spray area to be worked generously. Reapply as necessary to keep work area cool and well lubricated.

Health	1
Flammability	2
Physical Hazard	0
Protection	B

Areas of Use:

- *Bottling Plants
- *Steel Mills
- *Parks & Recreation
- *Cities & Counties
- *Factories
- *Refineries
- *Municipalities

Appearance & Odor.....	N/A
VOC%.....	15.00000%
Net Contents.....	14 OZ (396 Grams)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631