

FORMULA 86'D

Granulated Drain Opener/Maintainer
Sewer Solvent with Aluminum Pellets



This granular product is designed to remove fat and grease deposits in sewer and drain lines. The powerful chemical solvent in **FORMULA 86'D** is augmented by its catalytic and penetrating action. Other drain openers may generate heat, but will quickly cool down allowing grease and sludge to re-solidify. **FORMULA 86'D** has aluminum chips to absorb heat and distribute it evenly thereby making the product perform for longer periods and improve effectiveness farther down the drain line. **FORMULA 86'D** can be used on a regular preventive maintenance schedule to prevent buildup. For garbage disposal maintenance and grease clogs, use Omega's **NATURAL WAY** drain maintainer and degreaser.

DIRECTIONS

FOR SMALL DRAINS: Remove any standing water and pour 1 ounce of **FORMULA 86'D** into drain, add 1 cup of cold water. Wait 15 minutes then flush drain with cold water.
FOR FLOOR DRAINS: Increase dosage to 3 ounces and 3 cups of cold water.
FOR MAIN LINES: 4" to 8" in diameter, use entire container. This will help remove feeder roots without damage to the tree. Not recommended for use in toilets, dishwashers, garbage disposals, or appliances.

Health	3
Flammability	0
Physical Hazard	0
Protection	-

Areas of Use:

- *Municipalities
- *Plumbers
- *Sewer Departments
- *Apartments
- *Casinos
- *Theatres
- *Amusement Parks

Appearance & Odor.....	White powder with faint odor
VOC%.....	0%
Net Contents.....	2 LBS.

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631