

JELL STRIP II

Heavy Duty
Paint Stripper



JELL STRIP II is a heavy duty gel-based paint stripper formulated to cling to vertical surfaces if needed. This fast working formula penetrates quickly to remove paint, primers, varnish, carbon deposits, baked enamels, lacquer and silicone. Restores parts that have been improperly painted. Also removes coatings and industrial films before being painted. Safe to use on concrete, iron, steel, aluminum, copper, brass, and many other metals within normal contact time. Not for use on plastics or fiberglass.

- Clings to vertical surfaces – will not run.
- Works on porous and non-porous surfaces.
- May soften some plastics and paints.

DIRECTIONS SHAKE WELL BEFORE USING

1. Shake can vigorously for one minute after mixing ball begins to rattle.
2. Spray 8 to 12 inches from surface.
3. Allow several minutes to penetrate – for stubborn marks, use a stiff brush to agitate before wiping or rinsing.
4. Repeat above if necessary

Health	4
Flammability	1
Physical Hazard	0
Protection	B

Areas of Use:

- *Auto Detailers
- *Engine Rebuilders
- *Factories
- *Hospitals
- *Paint Shops
- *Painters
- *Schools
- *Sign Builders

Appearance & Odor.....	Clear gel with a pungent odor
VOC%.....	25.50%
Net Contents.....	18 OZ (510 GRAMS)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631