

MEGA LIFT

Floating Lift Station Degreaser



MEGA LIFT is formulated with soy bean oil derivatives, D-Limonine and natural corn surfactants. **MEGA LIFT** emulsifies and degreases raw sewage as it floats into lift station wells. The accumulation of sewage, grease, oils, fatty acids, calcium and soap scum form deposits on wet well walls. **MEGA LIFT**, by nature's own power, liquefies and attacks grease so it flows away. **MEGA LIFT** leaves a pleasant light citrus scent that effectively controls offensive odors. Add **MEGA LIFT** directly to lift station wet wells, grease traps and sump stations in its concentrated form for effortless cleaning. Degreasing and cleaning is accomplished by the rise and fall of the water level. As the water level rises and lowers, **MEGA LIFT** removes the sludge from the sides of the walls, then "seals and contains" offensive odors from the lift station and totally eliminates the offensive job of cleaning lift station grease traps or sumps manually.

DIRECTIONS

Grease Traps: For optimum results in the treatment of 1,000 gallon grease traps, it is best to pump the trap before treatment. For initial treatment of grease traps pour 2-4 gallons of **MEGA LIFT** into trap, then treat grease trap daily with 1-3 pints of **MEGA LIFT** depending on size of trap. For traps that have not been previously treated, an initial 5-10 gallons of **MEGA LIFT** will be needed.

Drains: Use **MEGA LIFT** a minimum of 4 times daily on all floors of building. Start on lowest floor of building at the rate of one floor per day until top floor is reached. When top floor is reached, continue treatment of top floor only. Use 2 times per week. Recommended use for 4" pipes is approximately 8 ounces per treatment.

Lift Station: **MEGA LIFT** should be added to a wet well until a layer of 8-10 inches is floating on the surface. This initial treatment should remain effective for a period of 3 to 6 months, depending on system demands. Add as needed.

Health	1
Flammability	2
Physical Hazard	1
Protection	B

Areas of Use:

- *Hotels
- *Schools
- *Cities & Counties
- *Hospitals
- *Parks & Recreation
- *Office Buildings
- *Water Treatment Facilities
- *Restaurants

Appearance & Odor.....	Orange liquid with citrus odor
Net Contents.....	5, 20, 30, 55 Gallons

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631