

MEGA STRIP

Easy To Use Wax Stripper



MEGA STRIP chemically liquifies tough acrylic cross linked floor finishes for easy pick up with minimum scrubbing. **MEGA STRIP** cleans and strips in one step, saving time and labor. It takes the long hours and backaches out of floor stripping. Simply mix, spray-on, scrub and vacuum off/mop off. It is your best attack against tough, metallic interlock finish build up. **MEGA STRIP** can be diluted with up to 8 parts of water for added economy. It will not soften asphalt or vinyl tiles like some other strippers. **MEGA STRIP** strips rubber, vinyl, vinyl asbestos, ceramic and quarry tile, marble, terrazzo and concrete. **MEGA STRIP** has a pleasant fragrance with no ammonia or other irritating after smell. It's biodegradable too.

DIRECTIONS

You don't need to strip every six to twelve months. Stripping is only necessary in four situations. The first would be if you were going to change from a buable to a non-buffable floor finish. The second is to prevent compatibility problems if you change suppliers. The third is if your floor has a heavy buildup of old discolored wax or polish. The fourth is if you have a new floor that still has the factory applied protective coating on it. If your floors fall into one of the categories listed above, then follow these procedures to strip and prepare them for coating.

Equipment Needed: Dust mop or push broom, towels, black stripping pads, single brush floor machine, three mop buckets and wringers, three synthetic mops and handles, abrasive pad or brush and handle, **MEGA STRIP**, measuring cup and wet vacuum. If you have a large building consider investing in an Auto-scrubber. This will significantly cut labor cost.

PROCEDURES

Step 1: Sweep away all loose dirt and trash. **Step 2:** Place towels in all doorways and entryways. **Step 3:** Place a black strip pad under a single brush floor machine and dry hone heavy build up along edge and baseboards. **Step 4:** Mix **MEGA STRIP** solution with hot water (120°F to 140°F) for best result as follows: **Heavy buildups:** Dilute 1 to 1 with hot water. **Medium buildups:** Dilute 1 to 2 with hot water. **Light buildups:** Dilute 1 to 4 with hot water. **Step 5:** Apply a liberal amount of the **MEGA STRIP** solution to an area approximately 10 feet by 20 feet. Allow 5 minutes dwell time or until the finish is liquified. **IMPORTANT:** Do not let the **MEGA STRIP** dry on the floor. **Step 6:** Place a back strip pad in the bucket of stripping solution to soak. Slowly rotate the pad until it's saturated.

Health	2
Flammability	0
Physical Hazard	0
Protection	-

Areas of Use:

- *Housing Authorities
- *School Districts
- *Cities & Counties
- *Office Buildings
- *Kennels
- *Public Buildings
- *Warehouses
- *Prisons
- *Shopping Malls
- *Veterinary Clinics

Appearance & Odor.....	Red liquid with fruity odor
Specific Gravity.....	1.04 @ 20°C
Net Contents.....	1 Gallon, 5 Gallon Pail

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631