

# OMEGA ASPHALT PATCH



## Driveway Patching Compound



**OMEGA ASPHALT PATCH** is a ready to use compound that can be applied to pot holes and depressions in any solid base, such as asphalt, concrete, brick, stone or wood. It is ready to use and does not need any heating or mixing preparation. It is made from a combination of hard aggregate, asphalt, resins and wetting agents to match original blacktop surfaces. Tamped into place, it is ready for traffic at once. **OMEGA ASPHALT PATCH** can be applied to either wet or dry surfaces in any temperature from hot to sub-freezing. The particles in **OMEGA ASPHALT PATCH** are smaller than other patching compounds, therefore it will not re-crush under pressure and recreate the hole you have just filled. Provides a much more permanent repair than bagged products.

### DIRECTIONS

Area to be patched must be free from dust, dirt, oil, grease and foreign matter. Spread the compound into areas to be patched. Tamp it in place or roll it in with a car. Areas exceeding one inch depth should be repaired in one inch increments. Use Omega's **NATURAL WAY** for effortless clean up of tools, vehicles and other surface contacted by **OMEGA ASPHALT PATCH**. Five gallons covers 5 sq. ft. at 1" thick. Shelf life 12 months.

Health	1
Flammability	1
Physical Hazard	0
Protection	**

### Areas of Use:

- \*Cities & Counties
- \*School Districts
- \*Apartment Complexes
- \*Street Departments
- \*Building Maintenance
- \*Construction Companies

Appearance & Odor..... Granular black coated stone material with petroleum odor  
 Net Contents..... 5 Gallons

## OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 307-514-0631