

OMEGA P.D.S.

Pourable Driveway Sealer



OMEGA P.D.S. is a fast drying, rubberized compound for use on the repair of asphalt roads, driveways, pavements, expansion joints and walkways. Speeds up seal coating jobs with quick drying. Provides a long term flexible repair on cracks and joints up to 3/4" wide. Also seals foundation walls and other pavement surfaces. Dries to dark black finish.

PREPARATION

Surfaces should be cleaned with **MEGA POWER** a cleaner and degreaser and free of any loose materials, grease, oil and dirt, before filling cracks. Rinse area thoroughly with a high pressure hose and allow to dry.

APPLICATION

Make sure top is secured and shake thoroughly. Unscrew top and flip over spout. Cut tip on a 45° angle to desired opening (for smaller amounts cut closer to top). Pour into crack filling slightly higher to allow for settling, but do not overfill. Allow 1 hour at good drying conditions (ie: above 65°F and under 50% relative humidity) prior to coating with a premium driveway sealer.

Note: Humidity and cool air/surface temperatures may lengthen cure time. Make sure filler has cured before sealing. Do not apply if rain is expected within 24 hours. **DO NOT HEAT.**

FOR BEST RESULTS

Apply when weather temperature is at least 65°F and rising.

CLEAN-UP

Clean tools with soap and water when wet. Dried **P.D.S.** may be removed with **NATURAL WAY** a citrus based cleaner

COVERAGE

1 Gal will fill approx. 75 liner feet of 1/4" cracks.

Health	1
Flammability	0
Physical Hazard	0
Protection	B

Areas of Use:

- *Apartment Complexes
- *School Districts
- *Cities & Counties
- *Grounds Maintenance
- *Dock Areas/Shipyards
- *Amusement Parks
- *Construction Companies

Appearance & Odor.....	Paste
VOC%.....	26 - 28%
Net Contents.....	1 US Gallon (3.79 L)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631