

# PERMA-TAPE

Heavy Duty All Purpose  
Tape & Sealant



**PERMA-TAPE** is a versatile and easy to use repair material, reinforcement, construction tape and sealant. Through the use of NanoShield surface protection and NanoSealant® SPP (self penetrating and priming) adhesive technology, this tape provides a multifunctional, all in one, easy to use product for residential, commercial and industrial applications. **PERMA-TAPE** will immediately seal materials stopping infiltration of leaks from air, moisture and water. **PERMA-TAPE** adheres to almost anything including metal, wood, fiberglass, plastic, structural concrete, concrete block, brick, Hypalon and PVC surfaces. **PERMA-TAPE** is easy to apply, forms an incredibly tough and durable repair and will provide a lifetime of dependability.

#### PREPARATION

- **General** - Substrate should be clean, dry and free of dew, frost, oil, salt, dust and rust.
- **Silicone** - Do not apply over silicone coatings or sealants.
- **PVC / Plastic** - Remove chalking with light sanding or scouring prior to application. Course sand paper or steel wool can be used.
- **Gravel** - Spud all embedded gravel on Gravel BUR before applying. Remove all rust with wire brush.

#### COLD / HOT WEATHER TIPS

In cold weather, allow **PERMA-TAPE** to remain inside at ambient room temperature (65-75°F) before application. In hot weather, keep **PERMA-TAPE** out of direct sunlight and in shade. Pre-peel edges approx. ½" to speed installation.

#### APPLICATION

1. Cut **PERMA-TAPE** to length. Shorter lengths (less than 4 ft) are easier to work with unless using a team of two or more applicators. 2. Hold edge of tape with thumb and index finger of both hands about 1-2 inches apart. Repeatedly wiggle tape ends back and forth scrunching the end of tape. Watch for edge of release liner to loosen away from tape and peel back release liner. 3. Press **PERMA-TAPE** in place using a gloved hand or a steel roller. Always roll from the center out to remove trapped air pockets and fishmouths. 4. Apply the exact length to predetermined location as tape cannot be peeled up and reset. 5. Puncture air pockets in tape and cut out tape wrinkles before continuing. Reseal puncture and cuts. When working in corners, start in corners to eliminate "tenting". **Available in Black or White.**



#### Areas of Use:

- |            |              |
|------------|--------------|
| *Roofs     | *Doors       |
| *Gutters   | *Flashings   |
| *Skylights | *Walls       |
| *Windows   | *Foundations |

Appearance & Odor.....	Solid rolls with gray adhesive
Net Contents.....	1 - 4" x 50' Roll

## OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 307-514-0631