

PLASTIKMAN

Plastic Repair Putty



PLASTIKMAN can be used to rebuild rigid and semi-threadable plastics, repair automotive trim or plastic furniture, and to seal leaks in plastic plumbing pipes. **PLASTIKMAN** forms a durable bond to all major plastic types except ployoletim (polyethylene /phypropylene), and can be molded into any shape, drilled, sanded and painted. Great when fast repairs are needed for high use areas. Work life is 25 minutes and final cure is only 3 hours. **PLASTIKMAN** has a 300 volt di-electric strength. For other surface repairs please also try Omega's **STEELMAN**, **CONCRETEMAN**, and **WOODMAN** repair putty.

DIRECTIONS

For best results, clean and roughen area to be repaired by sanding or filing. Twist off desired amount of **PLASTIKMAN** and knead into a uniform color. Apply at once as hardening begins immediately. For a smooth finish, hand rub with tap water or use damp cloth or tool prior to hardening. Wash hands and tools after use to remove any residue. Omega's **MUSCLEMAN** hand towels are a convenient way to clean hands and tools anywhere, anytime. No water needed.

Health	3
Flammability	0
Physical Hazard	0
Protection	-

Areas of Use:

- *Plumbing Departments
- *Water Treatment
- *Sewer Departments
- *Apartment Complexes
- *HVAC
- *Building Maintenance
- *School
- *Golf Courses

Appearance & Odor.....	Solid, odor and color not available
Relative Density.....	1.79

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631