

PLUG IT

Emergency Spill Control



PLUG IT seals off gasoline, diesel, solvents and other chemicals (hydrocarbons). **PLUG IT** seals immediately and sticks to dirty, crumpled surfaces even with the fluid flowing out. No surface preparation is required. **PLUG IT** will plug up to 3 feet of head (1.5 psi) even if the liquid is flowing out. Not recommended for some bio-fuels, and other chemicals such as strong acids, caustics and oxidizers. **PLUG IT** can be used to plug a 6-inch diameter hole and a slit 1 inch by 2 feet. **PLUG IT** is intended as an immediate temporary seal.

DIRECTIONS

No surface preparation is necessary. Put on latex gloves. Take a handful of **PLUG IT** and apply it directly into and around the edges of the leak. The initial contact of Plug It may only partly adhere to the surface. Work it and press down to get good adhesion. Apply enough **PLUG IT** to get a good thick layer over the leak. Additional **PLUG IT** can be added over the top. Do not use **PLUG IT** on Urethane or Teflon surfaces. Non-Toxic and Non-Flammable. Store above freezing. Remove any contaminated materials from inside container before closing tightly after use.

Health	0
Flammability	0
Physical Hazard	0
Protection	-

Appearance & Odor.....	Gray heavy paste-like consistency
Specific Gravity.....	Concentrate - 1.4
Net Contents.....	1 pound

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631