

PRIMAL PRIMER LIGHT GRAY

Primer Coating



PRIMAL PRIMER is a rust proof industrial primer formula that gives twice the coverage of conventional aerosol primers. **PRIMAL PRIMER** is heat resistant, VOC compliant and fast drying.

DIRECTIONS

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C.).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn spray head 1/4 turn or remove and clean spray head slot. Do not stick pin or other objects into can opening. With can and spray head pointed away from you, reinsert spray head with a gentle twisting motion.
5. To clear spray head for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

DRY TIME*:

To touch 5 minutes

To recoat 20 minutes

*At 72F, 50% humidity,

1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Health	1
Flammability	4
Physical Hazard	3
Protection	-

Areas of Use:

- *Cities & Counties
- *Hotels
- *Schools
- *Public Buildings
- *Amusement Parks
- *Stadiums
- *Apartments

Appearance & Odor.....	Aerosol with aromatic odor
VOC%.....	50.5%
Net Contents.....	17 OZ. (482 g)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631