

PROTECT ALL

Weather Protection



PROTECT ALL can be applied to any surface to provide a waterproof flexible permanent rubber film that will act as a barrier against moisture causing rust & corrosion on electrical connections. Once applied area becomes impervious to humidity, salt and fungus. Dries crystal clear and will not discolor or harm any surface. **PROTECT ALL** protects against water, dirt, wind, airborne particles and foreign elements.

DIRECTIONS

Shake container well before and during use. Due to the amount of rubber, the nozzle may on occasion sputter or momentarily clog, continue to spray, clogging will clear after a few seconds. Peel away any accumulation from nozzle tip. Wires and terminals to be sealed must be clean and dry. Spray **PROTECT ALL** on electrical connection area. Allow to dry for 15 minutes. Apply second coat if greater thickness is required or needed.

NOTE: Not to be sprayed on running Electrical motors or Live Wires. Disconnect all electrical equipment before using. Allow sufficient time to dry before reconnecting electrical equipment.

EXAMPLE: A 1/8" thick coating of properly applied **PROTECT ALL** will withstand up to 9,500 volts. A 1/16" coating of properly applied **PROTECT ALL** will withstand up to 4,750 volts.

Health	N/A
Flammability	N/A
Physical Hazard	N/A
Protection	N/A

Areas of Use:

- *Shipyards
- *Municipalities
- *Electrical Shops
- *Utilities
- *Around Electrical Boxes
- *Schools

Appearance & Odor.....	Clear coating
VOC%.....	MIR 1.50
Net Contents.....	11 OZ

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631