

RUST X

Rust Converter and
Metal Primer



RUST X is the quick and convenient way to treat rusted surfaces. This product chemically converts the rust to an inert black polymer based coating that prevents future rust from forming. Eliminates the need for brushing, sandblasting or scraping before painting rusted surfaces. Once treated, surface may be left unpainted or may be painted for improved appearance and protection. May be used on all rusted surfaces. Convenient spray can allows for quick, mess-free application. Combines a unique fast drying carrier with special rust converting agents and a strong polymeric coating.

DIRECTIONS

For best results, remove loose particles of rust and debris using a wire brush or rag. Be sure surface to be treated is dry and free of water. Shake can for 30 seconds before application. Remove protective cap and point opening in spray tip towards surface to be treated. Using a slow sweeping motion and holding can 8–12 inches from surface apply a thin coat covering all of the rusted area. Allow to dry. The surface will turn black. Apply a second thin coat. Allow surface to dry for 48 hours to promote complete curing of the polymeric coating. For additional protection apply 1 or 2 coats of a suitable spray paint. Apply the product when temperatures are between 50°F and 95°F. Store in a cool, dry area where temperatures are below 100°F.

Health	2
Flammability	4
Physical Hazard	1
Protection	B

Areas of Use:

- *Awnings
- *Docks & Ships
- *Parking Meter Posts
- *Industrial Equipment
- *Bottling/Packing Equipment
- *School Districts
- *Amusement Parks
- *Valves & Fittings

Appearance & Odor.....	Clear brown aerosol with solvent odor
VOC%.....	44%
Net Contents.....	13 oz.

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631