

TRUCK BED COATING



Textured Truck Bed Coating



TRUCK BED COATING is a thick, durable black sealant that forms a protective skin that is both tough and flexible. **TRUCK BED COATING** protects against corrosion and abrasion, withstands impacts, provides improved traction, and resists water. **TRUCK BED COATING** greatly extends equipment and vehicle life expectancy. **TRUCK BED COATING** is heat resistant up to 300°F can be used on truck beds, trailers, vehicle panels, wheel wells, and repair existing liner coatings.

DIRECTIONS

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C.).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn spray head 1/4 turn or remove and clean spray head slot. Do not stick pin or other objects into can opening. With can and spray head pointed away from you, reinsert spray head with a gentle twisting motion.
5. To clear spray head for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. **DO NOT** incinerate or compact.

Health	1
Flammability	4
Physical Hazard	3
Protection	-

Areas of Use:

- *Fleet Services
- *Schools
- *Cities & Counties
- *Municipalities
- *Construction Crews
- *Road Repair Equipment

Appearance & Odor.....	Aerosol with aromatic odor
Relative Density.....	Between 0.77 and 0.85 (Water equals 1.00)
Net Contents.....	15 oz.

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631