

Armor Coat

Stainless Steel Coating



ARMOR COAT has a super tough long-lasting coat containing 100% pure 316L stainless steel pigment in an ultra durable resin system, heat resistant up to 250°F and rust protection. Seals, beautifies and protects metal, wood, ceramics and more. **ARMOR COAT** helps prevent deterioration caused by harsh chemicals, severe atmospheres or conditions. Tack free in 5 minutes, hard cure in 2 hours.

Directions: 1.) Surface must be clean and dry before painting. For best results, use when can is between 50° and 90°F. 2.) Shake can at least one minute before and occasionally during use. 3.) Spray surface with steady even strokes at a distance of 8 to 10 inches. Several light coats give a better finish than one heavy coat. 4.) If clogging develops, turn spray button 1/4 turn or remove and clean button slot. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion. 5.) To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

Areas of Use:

- *Radiators
- *Steam pipes
- *Fire hydrants
- *Exhausts
- *Mufflers
- *Parking meters
- *Chain and wire fences
- *Boilers
- *Engines
- *Grills
- *Lockers
- *Heat exchangers
- *Oven storage and mixing tanks
- *Chemical processing and production equipment
- *Vehicle maintenance
- *HVAC trades
- *Marine agriculture
- *Food processing plants

Health	1
Flammability	4
Physical Hazard	3
Protection	-

Appearance and odor.....	Aromatic odor.
Specific Gravity.....	0.77 - 0.85
VOC.....	58.2%

Omega Industrial Supply, Inc.

Fairfield, CA 94534
1-800-571-7347 www.onlyomega.com Fax: 707-864-8134