

O.G.L.



Open Gear Lubricant



O.G.L. is a tacky spray lubricant that penetrates deep into gears, cables and heavy duty mechanism. Forms a protective water-resistant coating to prevent corrosion in outdoor applications. **O.G.L.** provides an elastic retractable film that reapplies itself with each revolution or movement of the lubricated part. **O.G.L.** penetrates into gears and cables where it sets up and bonds creating a shield to parts, maintaining a cushioning of lubricant between gear teeth and other friction-producing surfaces that will not drip or be thrown off. **O.G.L.** absorbs high shock loads, extreme pressure and prevents chipping and scuffing. Will not wash off, dry out, crap or peel. **O.G.L.** will NOT sling off, drip, melt, dry out or build between gear teeth. To clean up overspray or to remove old lubricant before application, use Omega's **NATURAL WAY** heavy duty degreaser.

Directions: SHAKE WELL. Shake vigorously for one minute after agitator ball begins to rattle. Spray liberally in short burst from 12" to 15". Repeat as needed.

Health	2
Flammability	3
Physical Hazard	0
Protection	B

Areas of Use:

- *Hotels
- *Schools
- *Cities & Counties
- *Restaurants
- *Stadiums
- *Casinos
- *Amusement Parks

Appearance & Odor..... Not Available.
 Net Contents..... 14 oz. (396 g)

Omega Industrial Supply, Inc.

Fairfield, CA 94534
1-800-571-7347 www.onlyomega.com Fax: 707-864-8134