

This brief provides a general overview of the Safety Data Sheet requirements in the Hazard Communication Standard OSHA's 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200).

Section 1 ~ Identification

Identity (As Used On Label and List)

A1060Y SAFE STEP YELLOW

Date Prepared:

02-19-2016

Company Information:

OMEGA INDUSTRIAL SUPPLY, INC

Emergency Telephone Number:

1-800-424-9300

Address (Number, Street, Suite/Apt#)

101 Grobric Ct #1

Telephone Number for Information:

1-800-571-7347

(City, State, and Zip Code)

Fairfield, CA 94534

Signature of Prepare (Optional)

REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Physical Hazards

Flammable Aerosols

Category 1

Health Hazards

Serious eye damage/eye irritation

Category 2A

Reproductive toxicity (the unborn child)

Category 2

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Specific target organ toxicity, repeated exposure

Category 2

Aspiration hazard

Category 1

OSHA Defined Hazards

Not classified

Label elements



Signal Word: Danger

Hazard Statement

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement
Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If Swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. **If Inhaled:** Remove person to fresh air and keep comfortable for breathing. **If In Eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental Hazards

Hazardous to the aquatic environment, acute hazard

Category 3

Hazard(s) Not Otherwise Classified

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Supplemental Information

None

Section 3 ~ Composition/Information on Ingredients

Mixtures

Components (Specific Chemical Identity, Common Name(s))

CAS No.

%(Wt.)

Acetone

67-64-1

20 - 40

Propane

74-98-6

10 - 20

Butane

106-97-8

2.5 - 10

Ethylene Glycol Propyl Ether

2807-30-9

2.5 - 10

Propylene Glycol Monomethyl Ether Acetate

108-65-6

2.5 - 10

Titanium Dioxide

13463-67-7

2.5 - 10

Toluene

108-88-3

2.5 - 10

Other components below reportable levels

-

20 - 40

* Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISONCENTER or doctor/physician if you feel unwell.

Skin Contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most Important Symptoms/Effects, Acute And Delayed: Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

Indication Of Immediate Medical Attention And Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General Information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Alcohol resistant foam, Powder, Carbon dioxide (CO2).

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising From The Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special Protective Equipment And Precautions For Fire-Fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment And Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods And Materials For Containment And Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. **Small Spills:** Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental Precautions: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Level 2 Aerosol.

Conditions for Safe Storage, Including Any Incompatibilities: Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|-----------------------------------|------|------------------------|------------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 1000 ppm | |
| Propane (CAS 74-98-6) | PEL | 1800 mg/m3 1000 ppm | |
| Titanium Dioxide (CAS 13463-67-7) | PEL | 15 mg/m3 | Total Dust |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|------------------------|----------------|--------------------|------|
| Toluene (CAS 108-88-3) | Ceiling TWA | 300 ppm 200 ppm | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|-----------------------------------|-------------|--------------------|------|
| Acetone (CAS 67-64-1) | STEL TWA | 500 ppm 250 ppm | |
| Butane (CAS 106-97-8) | STEL | 1000 ppm | |
| Titanium Dioxide (CAS 13463-67-7) | TWA | 10 mg/m3 | |
| Toluene (CAS 108-88-3) | TWA | 20 ppm | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|------------------------|-------------|--|------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m3 250 ppm | |
| Butane (CAS 106-97-8) | TWA | 1900 mg/m3 800 ppm | |
| Propane (CAS 74-98-6) | TWA | 1800 mg/m3 1000 ppm | |
| Toluene (CAS 108-88-3) | STEL TWA | 560 mg/m3 150 ppm 375 mg/m3 100 ppm | |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value |
|--|------|--------|
| Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) | TWA | 50 ppm |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|------------------------|------------------------------------|---|---------------------------------------|---------------|
| Acetone (CAS 67-64-1) | 25 mg/l | Acetone | Urine | * |
| Toluene (CAS 108-88-3) | 0.3 mg/g 0.03 mg/l 0.02 mg/l | o-Cresol, with hydrolysis Toluene Toluene | Creatinine in urine Urine Blood | * * * |

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin Designation

Propylene Glycol Monomethyl Ether Acetate (CAS108-65-6) Can be absorbed through the skin.
Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz. Subs: Skin Designation Applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual Protection Measures, Such As Personal Protective Equipment

Eye/Face Protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other: Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical Chemical Properties

Appearance and Odor: Gas. Aerosol. Odor Not available.

pH: N/A

Melting/Freezing Point: N/A

Initial Boiling Point/Boiling Range: 94.28°F (34.6°C) Estimated

Flash Point: -2.2°F (-19.0°C) Supplier

Evaporation Rate: N/A

Flammability (solid, gas): N/A

Flammability Limit - Lower: N/A

Flammability Limit - Upper: N/A

Vapor Pressure: 2750 hPa @70°F estimated

Vapor Density: N/A

Relative Density: N/A

Solubility (Water): N/A

Partition Coefficient (n-octanol/water): N/A

Auto Ignition: N/A

Decomposition Temperature: N/A

Viscosity: N/A

Explosive Properties: Not explosive

Oxidizing Properties: Not oxidizing

Specific Gravity: 0.85 Estimated

Section 10 ~ Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility Of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions To Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible Materials: Strong acids. Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous Decomposition Products: No hazardous decomposition products are known.

Section 11 ~ Toxicological Information

Information On Likely Routes Of Exposure

Inhalation: May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin Contact: No adverse effects due to skin contact are expected.

Eye Contact: Causes serious eye irritation.

Ingestion: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms Related To The Physical, Chemical And Toxicological Characteristics: Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on Toxicological Effects

Acute toxicity: May be fatal if swallowed and enters airways. Narcotic effects.

| <u>Components</u> | <u>Species</u> | <u>Test Results</u> | <u>Components</u> | <u>Species</u> | <u>Test Results</u> |
|---|----------------|--|---|----------------|---|
| Acetone (CAS 67-64-1) | | | Propane (CAS 74-98-6) | | |
| Acute | | | Acute | | |
| Dermal LD50 | Guinea pig | > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours | Inhalation LC 50 | Mouse | 1237 mg/l, 120 Minutes 52%, 120 minutes |
| | Rabbit | > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours | | Rat | 1355 mg/l 658 mg/l/4h |
| Inhalation LC50 | Rat | 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l | Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) | | |
| Oral LD50 | Rat | 5800 mg/kg 2.2 ml/kg | Acute | | |
| | | | Dermal LD50 | Rat | > 2000 mg/kg, 24 Hours |
| Butane (CAS 106-97-8) | | | Oral LD50 | Rat | >5000 mg/kg > 14.1 ml |
| Acute | | | Titanium Dioxide (CAS 13463-67-7) | | |
| Inhalation LC50 | Mouse | 1237 mg/l, 120 Minutes 52 %, 120 Minutes | Acute | | |
| | Rat | 1355 mg/l | Inhalation LC50 | Rat | > 2.28 mg/l, 4 hours |
| | | | Oral LD50 | Mouse | > 5000 mg/kg |
| Ethylene Glycol Propyl Ether (CAS 2807-30-9) | | | | Rat | > 2000 mg/kg |
| Acute | | | Toluene (CAS 108-88-3) | | |
| Dermal LD50 | Guinea Pig | 5.6 g/kg, 4 Days | Acute | | |
| | Rabbit | > 1 g/kg, 24 Hours 1337 ml/kg, 14 Days | Dermal LD50 | Rabbit | > 5000 mg/kg, 24 Hours 6405-7436 ppm, 6 Hours |
| Inhalation LC50 | Rat | >2132 ppm, 6 hours >1800 ppm | Inhalation LC50 | Mouse | 5320 ppm, 8 Hours 5879-6281 ppm, 6 Hours 25.7 mg/l, 4 Hours |
| Oral LD50 | Guinea Pig | 2.2 g/kg | | Rat | > 5000 mg/kg |
| | Mouse | 1774 mg/kg | Oral LD50 | Rat | > 5000 mg/kg |
| | Rat | 0.5 - 1 g/kg | | | |

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Not applicable.

Serious Eye Damage/Eye Irritation: Causes serious eye irritation.

Respiratory Or Skin Sensitization

Respiratory Sensitization: Not a respiratory sensitizer.

Skin Sensitization: This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity: Titanium Dioxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens: Not listed.

Reproductive Toxicity: Suspected of damaging the unborn child.

Specific Target Organ Toxicity-Single Exposure: May cause drowsiness and dizziness.

Specific Target Organ Toxicity - Repeated Exposure: May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Chronic Effects: May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Section 12 ~ Ecological Information

Ecotoxicity: Harmful to aquatic life with long lasting effects.

| <u>Components</u> | <u>Species</u> | <u>Test Results</u> |
|---|----------------|---|
| Acetone (CAS 67-64-1) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) |
| | | 21.6 - 23.9 mg/l, 48 Hours 4740 - 6330 mg/l, 96 Hours |
| Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) | | |
| Aquatic | | |
| Crustacea | EC50 | Daphnia |
| | | 500.0001 mg/l, 48 hours |
| Titanium dioxide (CAS 13463-67-7) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) |
| Fish | LC50 | Mummichog (fundulus heterolitus) |
| | | > 1000 mg/l, 48 hours >1000 mg/l, 96 hours |
| Toluene (CAS 108-88-3) | | |
| Aquatic | | |
| Algae | IC50 | Algae |
| Crustacea | EC50 | Daphnia |
| | | 433.0001 mg/l, 72 Hours 7.645 mg/l, 48 Hours 5.46-9.83 mg/l, 48 Hours |
| Fish | LC50 | Water flea (Daphnia magna) Coho salmon, silver salmon (Oncorhynchus kisutch) |
| | | 8.11 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential

Partition coefficient n-octanol / water (log Kow): Acetone -0.24 Butane 2.89 Propane 2.36 Toluene 2.73

Mobility in soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations: Dispose in accordance with all applicable regulations.

Hazardous waste code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / Unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Section 14 ~ Transport Information

| US Depart. of Transportation (DOT) | Water Transportation (IMDG) | Air Transportation (IATA) |
|--|--|--|
| UN Number: UN1950 UN Proper Shipping Name: Aerosols, flammable Transport Hazard Class(es): Class: 2.1 Subsidiary Risk - Label(s): 2.1 Packing Group: Not applicable. Special Provisions: N82 Packaging Exceptions: 306 Packaging Non Bulk: None Packaging Bulk: None | UN Number: UN1950 UN Proper Shipping Name: AEROSOLS Transport Hazard Class(es): Class: 2.1 Subsidiary Risk - Label(s): 2.1 Packing Group: Not applicable. Environmental Hazards Marine Pollutant: No. Ems: F-D, S-U Packaging Exceptions LTD QTY Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable. | UN Number: UN1950 UN Proper Shipping Name: Aerosols, flammable Transport Hazard Class(es): Class: 2.1 Subsidiary Risk - Label(s): 2.1 Packing Group: Not applicable. Environmental Hazards: No. ERG Code: 10L Other Information Passenger And Cargo Aircraft: Allowed with restrictions. Cargo Aircraft Only: Allowed with restrictions. Packaging Exceptions: LTD QTY |

Special Precautions For User: Read safety instructions, SDS and emergency procedures before handling.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

DOT



IATA;IMDG



Section 15 ~ Regulatory Information

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4): Acetone (CAS 67-64-1) Listed.

Toluene (CAS 108-88-3) Listed.

SARA 304 Emergency Release Notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories Immediate Hazard – Yes Delayed Hazard – Yes

Fire Hazard – Yes

Pressure Hazard – No

Reactivity Hazard – No

SARA 302 Extremely Hazardous Substance: Not listed.

SARA 311/312 Hazardous Chemical: No

| SARAH 313 (TRI Reporting) | | |
|---------------------------|------------|----------|
| Chemical Name | CAS Number | % by wt. |
| Toluene | 108-88-3 | 2.5 - 10 |

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA), List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number:

Acetone (CAS 67-64-1) 6532 Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA), List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % WV Toluene (CAS 108-88-3) 35 % WV

DEA Exempt Chemical Mixtures Code Number: Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 594

US State Regulations

US, California Controlled Substances, CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US, California, Candidate Chemicals List, Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

US, Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

US, New Jersey Worker and Community

Right-to-Know Act

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

US, Pennsylvania Worker and Community

Right-to-Know Law

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

US, Rhode Island RTK

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US, California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed Date/Carcinogenic Substance:

Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental Toxin: Toluene (CAS 108-88-3) Listed: January 1, 1991

International Inventories Country(s) or Region

Australia

Canada

Canada

China

Europe

Europe

Japan

Korea

New Zealand

Philippines

United States & Puerto Rico

Inventory Name

Australian Inventory of Chemical Substances (AICS)

Domestic Substances List (DSL)

Non-Domestic Substances List (NDSL)

Inventory of Existing Chemical Substances in China (IECSC)

European Inventory of Existing Commercial Chemical Substances (EINECS)

European List of Notified Chemical Substances (ELINCS)

Inventory of Existing and New Chemical Substances (ENCS)

Existing Chemicals List (ECL)

New Zealand Inventory

Philippine Inventory of Chemicals and Chemical Substances (PICCS)

Toxic Substances Control Act (TSCA) Inventory

On inventory (yes/no)*

No

Yes

No

No

No

No

No

No

No

Yes

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

| | NFPA | HMIS | Key |
|------------------|------|------|-------------|
| HEALTH | 2 | *2 | 4= Severe |
| FLAMMABILITY | 4 | 4 | 3= Serious |
| REACTIVITY | 1 | 1 | 2= Moderate |
| OTHER/PROTECTION | - | X | 1= Slight |

Disclaimer: Omega Industrial Supply, Inc. We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.